


| | |
|--|---------------------------|
|  | Page: 1 |
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Derakane Momentum™ 411-350 epoxy vinyl ester resin
 ™ Trademark, Ashland or its subsidiaries, registered in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Reserved for industrial and professional use.

Restrictions on use

Consumer use

| | |
|---|---|
| <p>Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America (USA) +1-614-790-3333</p> <p>EHSProductSafety@ashland.com</p> | <p>Emergency telephone number 1-800-ASHLAND (1-800-274-5263)</p> <p>Regulatory Information Number 1-800-325-3751</p> <p>Product Information +1-614-790-3333</p> |
|---|---|

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Combustible Dust :

Skin irritation : Category 2

Eye irritation : Category 2A

Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

Specific target organ systemic toxicity - repeated exposure (Inhalation) : Category 1 (Auditory system)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.
May form combustible dust concentrations in air.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
Causes damage to organs (Auditory system) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.
Hazardous polymerization can occur under certain conditions.
Avoid excessive heat, direct sunlight, peroxides, and other polymerization catalysts. Store in a cool place and maintain proper concentrations of inhibitor and oxygen.

Response:
IF ON SKIN (or hair): Take off immediately all contaminated



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Get medical advice/ attention if you feel unwell.
 If skin irritation occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static Accumulating liquid
 Hazardous polymerization may occur.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Classification | Concentration (%) |
|---------------|----------|---|-------------------|
| STYRENE | 100-42-5 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 STOT RE 1; H372 Asp. Tox. 1; H304 | 43.964 |



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
IF INHALED: Call a POISON CENTER/ doctor if you feel unwell.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
confusion
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
Causes damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : No hazards which require special first aid measures.



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon dioxide (CO2)
Carbon monoxide
Burning produces noxious and toxic fumes.
Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Do not use a solid water stream as it may scatter and spread fire.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Polymerization will take place under fire conditions. If polymerization occurs in a closed container, there is a possibility it will rupture violently. Cool storage container with water, if exposed to fire.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and : Evacuate personnel to safe areas.
Remove all sources of ignition.



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

| | |
|---|--|
| emergency procedures | Use personal protective equipment. Ensure adequate ventilation. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |
| Other information | : Comply with all applicable federal, state, and local regulations. Suppress (knock down) gases/vapours/mists with a water spray jet. |

SECTION 7. HANDLING AND STORAGE

| | |
|-------------------------|--|
| Advice on safe handling | : Open drum carefully as content may be under pressure. Avoid formation of aerosol. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Container hazardous when empty. Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations. Secondary operations, such as grinding and sanding, may produce dust. Maintain good housekeeping. Do not permit dust layers to accumulate, for example, on floors, ledges, and equipment, in order to avoid any potential for dust explosion hazards. For further guidance on prevention of dust explosions, refer to |
|-------------------------|--|



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

National Fire Protection Association (NFPA) 654: "Standard for the Prevention of Fire and Dust Explosions, from the Manufacturing, Processing and Handling of Combustible Particulate Solids".

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|----------|-------------------------------|--|-----------|
| STYRENE | 100-42-5 | TWA | 50 ppm 215 mg/m ³ | NIOSH REL |
| | | ST | 100 ppm 425 mg/m ³ | NIOSH REL |
| | | TWA | 100 ppm | OSHA Z-2 |
| | | CEIL | 200 ppm | OSHA Z-2 |
| | | Peak | 600 ppm | OSHA Z-2 |
| | | TWA | 50 ppm 215 mg/m ³ | OSHA P0 |
| | | STEL | 100 ppm 425 mg/m ³ | OSHA P0 |
| | | C | 500 ppm | CAL PEL |
| | | PEL | 50 ppm 215 mg/m ³ | CAL PEL |
| | | STEL | 100 ppm 425 mg/m ³ | CAL PEL |
| | | TWA | 20 ppm | ACGIH |
| | | STEL | 40 ppm | ACGIH |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|------------|----------|--------------------|---------------------|------------------|---------------------------|----------------|
| STYRENE | 100-42-5 | Mandelic acid plus | Urine | End of shift (As | 400 mg/g Creatinine | ZUS_A CGIHB |



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

| | | | | | | |
|--|--|----------------------|-------|--|---------|----------------|
| | | phenylglyoxylic acid | | soon as possible after exposure ceases) | | |
| | | Styrene | Urine | End of shift (As soon as possible after exposure ceases) | 40 µg/l | ZUS_A CGIHB |

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.
Provide appropriate exhaust ventilation at places where dust is formed.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Filter type : Organic vapour type

Hand protection

Material : Laminate (Barrier© or Silvershield©)

Break through time : 480 min

Glove thickness : > 0.5 mm

Remarks : The exact break through time can be obtained from the protective glove producer and this has to be observed. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|------------------------------|--|
| Appearance | : liquid |
| Physical state | : liquid |
| Colour | : light yellow |
| Odour | : pungent |
| Odour Threshold | : No data available |
| pH | : No data available |
| Melting point/freezing point | : No data available |
| Boiling point/boiling range | : 293 °F / 145 °C Calculated Phase Transition Liquid/Gas |
| Flash point | : 29.4 °C Method: Seta closed cup |
| Evaporation rate | : < 1 Ethyl Ether = 1 |
| Flammability (solid, gas) | : May form combustible dust concentrations in air (during processing). |
| Flammability (liquids) | : Static Accumulating liquid |
| Upper explosion limit | : Upper flammability limit 6.1 %(V) Method: Calculated Explosive Limit |
| Lower explosion limit | : Lower flammability limit 1.1 %(V) Method: Calculated Explosive Limit |



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

| | |
|--|---|
| Vapour pressure | : 6.67 hPa (20 °C) Calculated Vapor Pressure |
| Relative vapour density | : > 1(Air = 1.0) |
| Relative density | : No data available |
| Density | : 1.078 g/cm ³ (25 °C) |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : > 20.5 mm ² /s (40 °C) |
| Oxidizing properties | : No data available |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : Stable under recommended storage conditions. |
| Possibility of hazardous reactions | : Hazardous polymerisation may occur. Vapours may form explosive mixture with air. This product does not present a dust explosion hazard as delivered. However, fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source, is a potential dust explosion hazard. |
| Conditions to avoid | : excessive heat Exposure to air. Exposure to sunlight. |



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

Heat, flames and sparks.

Incompatible materials : Acids
aluminum
aluminum chloride
Bases
Copper
Copper alloys
halogens
iron chloride
metal salts
Oxidizing agents
Peroxides

Hazardous decomposition products : Carbon monoxide
Carbon dioxide (CO₂)
Hydrocarbons
Acetone

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

STYRENE:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l, 2770 ppm
Exposure time: 4 h
Test atmosphere: vapour

No observed adverse effect level (Humans): 100 ppm
Exposure time: 7 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

STYRENE:

Species: Rabbit

Result: Irritating to skin.

Species: human skin

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

STYRENE:

Result: Irritating to eyes.

Remarks: Vapour during processing may be irritating to the respiratory tract and to the eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

STYRENE:

Exposure routes: Skin contact

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Result: negative

Exposure routes: inhalation (vapour)

Species: Humans

Assessment: Does not cause respiratory sensitisation.

Result: negative

Germ cell mutagenicity



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Product:

Carcinogenicity - Assessment : Styrene has been tested for carcinogenicity in rats and mice. Styrene caused lung tumors in mice only. These tumors are not considered to be relevant to humans.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

Components:

STYRENE:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs (Auditory system) through prolonged or repeated exposure if inhaled.

Components:

STYRENE:

Exposure routes: inhalation (vapour)

Target Organs: Auditory system

Assessment: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

STYRENE:

Species: Human

85 mg/m³

Application Route: inhalation (vapour)

Species: Human

615 mg/kg

Application Route: Skin contact

Aspiration toxicity

Not classified based on available information.

Components:

STYRENE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

Carcinogenicity:



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

| | |
|-------------|--|
| IARC | Group 2A: Probably carcinogenic to humans |
| | STYRENE 100-42-5 |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
| NTP | Reasonably anticipated to be a human carcinogen |
| | STYRENE 100-42-5 |

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment
Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 2; Toxic to aquatic life.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

STYRENE:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 4.02 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.7 mg/l
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 4.9 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.01 mg/l
Exposure time: 21 d

Toxicity to bacteria : EC50 (activated sludge): ca. 500 mg/l
Exposure time: 0.5 h

Toxicity to soil dwelling organisms : NOEC (Eisenia fetida (earthworms)): 34 mg/kg
Exposure time: 14 d
Method: OECD Test Guideline 207



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

Persistence and degradability

Components:

STYRENE:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 10 d

No data available

Bioaccumulative potential

Components:

STYRENE:

Bioaccumulation : Bioconcentration factor (BCF): < 100

Partition coefficient: n-octanol/water : log Pow: 2.96 (25 °C)

No data available

Mobility in soil

Components:

STYRENE:

Distribution among environmental compartments : Koc: 352

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

Components:

STYRENE:

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

**SAFETY DATA SHEET**

Revision Date: 03/13/2019

Print Date: 4/10/2019

SDS Number: R0402382

Version: 1.6

Derakane Momentum™ 411-350 epoxy vinyl ester resin
 ™ Trademark, Ashland or its subsidiaries, registered in various countries
 40210

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.
 Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|

MX_DG

| | | | | | |
|---------|----------------|---|--|-----|--|
| UN 1866 | RESIN SOLUTION | 3 | | III | |
|---------|----------------|---|--|-----|--|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

| | | | | | |
|---------|----------------|---|--|-----|--|
| UN 1866 | Resin solution | 3 | | III | |
|---------|----------------|---|--|-----|--|

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

| | | | | | |
|---------|----------------|---|--|-----|--|
| UN 1866 | Resin solution | 3 | | III | |
|---------|----------------|---|--|-----|--|

INTERNATIONAL MARITIME DANGEROUS GOODS

| | | | | | |
|---------|----------------|---|--|-----|--|
| UN 1866 | RESIN SOLUTION | 3 | | III | |
|---------|----------------|---|--|-----|--|

TDG INWT_C

| | | | | | |
|---------|----------------|---|--|-----|--|
| UN 1866 | RESIN SOLUTION | 3 | | III | |
|---------|----------------|---|--|-----|--|

TDG RAIL_C

| | | | | | |
|---------|----------------|---|--|-----|--|
| UN 1866 | RESIN SOLUTION | 3 | | III | |
|---------|----------------|---|--|-----|--|



| | |
|--|---------------------------|
| SAFETY DATA SHEET Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| | Version: 1.6 |

TDG ROAD C

| | | | | |
|----|------|----------------|---|-----|
| UN | 1866 | RESIN SOLUTION | 3 | III |
|----|------|----------------|---|-----|

U.S. DOT - INLAND WATERWAYS

| | | | | |
|----|------|----------------|---|-----|
| UN | 1866 | Resin solution | 3 | III |
|----|------|----------------|---|-----|

CFR RAIL C

| | | | | |
|----|------|----------------|---|-----|
| UN | 1866 | Resin solution | 3 | III |
|----|------|----------------|---|-----|

U.S. DOT - ROAD

| | | | | |
|----|------|----------------|---|-----|
| UN | 1866 | Resin solution | 3 | III |
|----|------|----------------|---|-----|

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

| | |
|------------------|----|
| Marine pollutant | no |
|------------------|----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION


**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|----------|--------------------|-----------------------------|
| STYRENE | 100-42-5 | 1000 | 2275 |

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

- SARA 311/312 Hazards** :
- Flammable (gases, aerosols, liquids, or solids)
 - Combustible Dust
 - Hazard not otherwise classified (physical hazards)
 - Skin corrosion or irritation
 - Serious eye damage or eye irritation
 - Specific target organ toxicity (single or repeated exposure)

| | |
|--|---------------------------|
|  | Page: 18 |
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|---------|----------|---------|
| STYRENE | 100-42-5 | 43.96 % |
|---------|----------|---------|

California Prop. 65

WARNING: This product can expose you to chemicals including styrene, benzene, 1,2-dihydroxybenzene; pyrocatechol, which is/are known to the State of California to cause cancer, and ethanediol; ethylene glycol, methanol, benzene, toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

- DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 03/13/2019

| | |
|--------------|------------------|
| NFPA: | HMIS III: |
|--------------|------------------|

**SAFETY DATA SHEET**


Revision Date: 03/13/2019

Print Date: 4/10/2019

SDS Number: R0402382

Version: 1.6

Derakane Momentum™ 411-350 epoxy vinyl ester resin
 ™ Trademark, Ashland or its subsidiaries, registered in various countries
 40210

**NFPA Flammable and Combustible Liquids Classification**

Flammable Liquid Class IC

Full text of H-Statements

| | |
|------|--|
| H226 | Flammable liquid and vapor. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H372 | Causes damage to organs through prolonged or repeated exposure if inhaled. |

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).



| | |
|--|---------------------------|
| SAFETY DATA SHEET | Revision Date: 03/13/2019 |
| | Print Date: 4/10/2019 |
| | SDS Number: R0402382 |
| Derakane Momentum™ 411-350 epoxy vinyl ester resin ™ Trademark, Ashland or its subsidiaries, registered in various countries 40210 | Version: 1.6 |

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative