Printing date 01/20/2011

Material Safety Data Sheet acc. to ISO/DIS 11014



Page 1/9

Reviewed on 01/20/2011

# 1 Identification of the substance/mixture and of the company/undertaking

- · Product details
- · Trade name: 68422 Mini-Max Bumper Repair
- Article number: 68422
- · Application of the substance / the preparation coating
- Manufacturer/Supplier: SEM Products Inc. 1685 Overview Drive Rock Hill, SC 29730 803 207 8225
- · Information department:

cust\_care@semproducts.com : SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

• Emergency information: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

## 2 Composition/information on ingredients

· Chemical characterization

• Description: Mixture of the substances listed below with nonhazardous additions.

66402-68-4	CERAMIC MICROSPHERES	13 - 30%
	♦ H315; H319; H335	
	Mercaptan Terminated Polymer	
	♦ H319; H335	
25068-38-6	bisphenolA(chloro)oxirane polymer	10 -13%
	🚸 H411; 🕦 H315; H319; H317	
28064-14-4	BISPHENOL F EPOXY RESIN	5 - 7%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1.5 - 5%
68909-14-8	ELASTOMER MODIFIED DIGLYCIDAL ETHER	1-1.5%
84-74-2	dibutyl phthalate	<u>≤1%</u>
	🚸 H360; 🚸 H400	
17557-23-2	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	<u>≤1%</u>
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	<u>≤1%</u>
	🛞 H300; H311; H332; H315; H319; H335	
SVHC		
84-74-2 dib	utyl phthalate	

(Contd. on page 2)

Material Safety Data Sheet SEM acc. to ISO/DIS 11014

Printing date 01/20/2011

Reviewed on 01/20/2011

Trade name: 68422 Mini-Max Bumper Repair

(Contd. of page 1)

3 Hazards identification
<ul> <li>Classification of the substance or mixture</li> <li>Classification according to Regulation (EC) No 1272/2008</li> </ul>
GHS08 Health hazard
H360 May damage fertility or the unborn child.
GHS07
<ul> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H335 May cause respiratory irritation.</li> </ul>
<ul><li>H333 May be harmful if inhaled.</li><li>H412 Harmful to aquatic life with long lasting effects.</li></ul>
Classification according to Directive 67/548/EEC or Directive 1999/45/EC Toxic May cause harm to the unborn child.
<ul> <li>Irritant</li> <li>Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.</li> <li>Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of international guidelines.</li> <li>Classification system: The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.</li> </ul>
<ul> <li>Label elements</li> <li>Labelling according to Regulation (EC) No 1272/2008</li> <li>Hazard pictograms</li> </ul>
GHS07 GHS08
· Signal word Danger
<ul> <li>Hazard-determining components of labelling: bisphenolA(chloro)oxirane polymer dibutyl phthalate quinuclidine Quartz (SiO2)</li> <li>Hazard statements May be harmful if inhaled. Causes skin irritation.</li> </ul>
Causes serious eye irritation. (Contd. on page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/20/2011

Reviewed on 01/20/2011

#### Trade name: 68422 Mini-Max Bumper Repair

(Contd. of page 2) May cause an allergic skin reaction. May damage fertility or the unborn child. May cause respiratory irritation. Harmful to aquatic life with long lasting effects. **Precautionary statements** Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

• *Labelling according to EU guidelines:* The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:



• Hazard-determining components of labelling: bisphenolA(chloro)oxirane polymer BISPHENOL F EPOXY RESIN 2,4,6-tris(dimethylaminomethyl)phenol dibutyl phthalate

· Risk phrases:

May cause harm to the unborn child. Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact.

· Safety phrases:

Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Wear suitable gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). This material and its container must be disposed of as hazardous waste.

- Special labelling of certain preparations: Contains epoxy constituents. See information supplied by the manufacturer.
- · Classification system:
- · NFPA ratings (scale 0 4)



(Contd. on page 4)

LIS A

*Page 4/9* 

(Contd. of page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/20/2011

Reviewed on 01/20/2011

Trade name: 68422 Mini-Max Bumper Repair

• HMIS-ratings (scale 0 - 4)

HEALTH2Health = 2FIRE1Fire = 1REACTIVITY0Reactivity = 0

### 4 First aid measures

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

## **5** Firefighting measures

• Suitable extinguishing agents: Use fire fighting measures that suit the environment.

· Protective equipment: No special measures required.

## **6** Accidental release measures

- · Person-related safety precautions: Not required.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- *Measures for cleaning/collecting:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

# 7 Handling and storage

· Handling:

- · Information for safe handling:
- No special measures required.
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)

Page 5/9

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 01/20/2011

Reviewed on 01/20/2011

Trade name: 68422 Mini-Max Bumper Repair

(Contd. of page 4)

# 8 Exposure controls/personal protection · Additional information about design of technical systems: No further data; see item 7. · Components with limit values that require monitoring at the workplace: 84-74-2 dibutyl phthalate PEL 5 $mg/m^3$ REL 5 $mg/m^3$ TLV 5 mg/m<sup>3</sup> • Additional information: The lists that were valid during the creation were used as basis. · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. · Eye protection: Tightly sealed goggles **9** Physical and chemical properties · General Information · Appearance: Form: Liquid Color: According to product specification

(Contd. on page 6)



Material Safety Data Sheet

Printing date 01/20/2011

Reviewed on 01/20/2011

#### Trade name: 68422 Mini-Max Bumper Repair

		(Contd. of page 5)
· Odor:	Characteristic	
• Change in condition Melting point/Melting range: Boiling point/Boiling range:		
· Flash point:	257°C (495°F)	
· Auto igniting:	Product is not selfigniting.	
• Danger of explosion:	Product does not present an explosion hazard. In use, may form flammable/explosive vapour-air mixture.	
• Density at 20°C (68°F):	1.62 g/cm <sup>3</sup> (13.519 lbs/gal)	
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
• Solvent content: Organic solvents: Water: VOC content:	0.0 % 0.1 % 4.0 g/l / 0.03 lb/gl	
Solids content:	99.8 %	

# **10 Stability and reactivity**

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• Materials to be avoided:

· Dangerous reactions No dangerous reactions known.

· Dangerous products of decomposition: No dangerous decomposition products known.

# **11 Toxicological information**

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

84-74-2 dibutyl phthalate

*Oral LD50 8000 mg/kg (rat)* 

Dermal LD50 20000 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 7)

USA

Printing date 01/20/2011

Material Safety Data Sheet

Reviewed on 01/20/2011

Trade name: 68422 Mini-Max Bumper Repair

(Contd. of page 6)

# **12 Ecological information**

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

## **13 Disposal considerations**

· Product:

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

# **14 Transport information**

- · DOT regulations:
- · Hazard class:
- Remarks NOT REGULATED

· Land transport TDG (Canada) and ADR/RID (Europe):

- Hazard class:
  Remarks:
  NOT REGULATED
- Maritime transport IMDG: • IMDG Class: -
- Marine pollutant: No
- Remarks: NOT REGULATED
- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -
- *Remarks:* NOT REGULATED
- · UN ''Model Regulation'': -

## **15 Regulatory information**

Sara
Section 355 (extremely hazardous substances): None of the ingredient is listed.
Section 313 (Specific toxic chemical listings): 68909-14-8 ELASTOMER MODIFIED DIGLYCIDAL ETHER 84-74-2 dibutyl phthalate 107-21-1 ethanediol 67-56-1 methanol

USA



Material Safety Data Sheet SEM acc. to ISO/DIS 11014

Printing date 01/20/2011

Reviewed on 01/20/2011

Trade name: 68422 Mini-Max Bumper Repair

TSCA (T	in Substances Control Action	(Contd. of pag
	ic Substances Control Act):	
	CERAMIC MICROSPHERES	
	GROUND CALCIUM CARBONATE	
	bisphenolA(chloro)oxirane polymer	
	BISPHENOL F EPOXY RESIN	
	2,4,6-tris(dimethylaminomethyl)phenol	
	titanium dioxide	
	ELASTOMER MODIFIED DIGLYCIDAL ETHER	
	dibutyl phthalate	
	FUMED SILICA	
	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	
	quinuclidine	
	3-aminopropyltriethoxysilane	
	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	
	ethanediol	
	YELLOW IRON OXIDE	
Proposition		
	known to cause cancer:	
	bisphenolA(chloro)oxirane polymer	
	BISPHENOL F EPOXY RESIN	
	ethanediol	
14808-60-7	Quartz (SiO2)	
	known to cause reproductive toxicity for females:	
None of the	ingredients is listed.	
<b>Chemicals</b>	known to cause reproductive toxicity for males:	
None of the	ingredients is listed.	
<b>Chemicals</b>	known to cause developmental toxicity:	
64-17-5 etl		
	nity categories	
-	conmental Protection Agency)	
-	putyl phthalate	
	rnational Agency for Research on Cancer)	
	titanium dioxide	
	silicon dioxide, chemically prepared	
	Quartz (SiO2)	•
-	nal Toxicology Program)	
	Quartz (SiO2)	
	hold Limit Value established by ACGIH)	
	titanium dioxide	2
	ethanediol	1
14808-60-7	Quartz (SiO2)	1
	ethanol	1

Material Safety Data Sheet

Printing date 01/20/2011

Reviewed on 01/20/2011

Trade name: 68422 Mini-Max Bumper Repair

(Contd. of page 8)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

14808-60-7 Quartz (SiO2)

67-56-1 methanol

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Chemical safety assessment A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environment protection department.

· Contact: Steve Gaver

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent