

PLUG IN WITH THE MOST AFFORDABLE TSO-CERTIFIED CHARGING PORT.

Enjoy the convenience of USB power in your aircraft — delivered by the durable, high-quality engineering that you expect with the Stratus name.



With enough power to charge two full-size iPads while they're in use, Stratus PowerTM can be used with any combination of portable electronic devices.

✓ NO RADIO NOISE

Stratus Power is radio-shielded, so you won't experience NAV/COM interference like you do with cheap electronics.

EASY TO INSTALL

Like all Stratus products from Appareo, Stratus Power was designed for quick and easy installation.

FEATURES

INCLUDES DUAL 2.5 AMP USB-A CHARGING PORTS

FAA CERTIFIED TO TSO-C71

CYLINDRICAL SHAPE FOR EASY DRILL-IN INSTALLATION

DESIGNED AND BUILT IN THE USA

TWO-YEAR PRODUCT WARRANTY, BACKED BY APPAREO

APPAREO



CHARGING PORT TYPE

USB Standard-A

INPUT VOLTAGE RANGE

10-32 VDC

INPUT CURRENT

<25 mA at 14V and 28V with no USB connections

0.95 amps at 28V at full output

load on both ports

1.9 amps at 14V at full output

load on both ports

USE WITH

2 amp breaker for 28V systems 4 amp breaker for 14V systems Inline fuse for either system **DIMENSIONS**

1.848" W x 1.848" H x 1.391" D (depth includes mating connector)

WEIGHT

OUTPUT VOLTAGE RANGE 5

MAX CURRENT OUTPUT

MOUNTING


CERTIFICATION


2.56 oz 5 VDC +/- 0.25V


2.5 amps per port

Rear panel mount

FAA TSO-C71 RTCA DO-160G







APPAREO

1810 NDSU Research Circle North Fargo, North Dakota 58102 USA 701.356.2200

