

Revision 1

MATERIAL SAFETY DATA SHEET U-10 Brake Cleaner

Supercedes: None

Revision Date: 8/19/08

Section 1 – Identification U-10 Brake Cleaner **Product Name:** Part Number: 06220. C06220 **Chemical Name:** Acetone/ Aliphatic Hydrocarbon mixture Product Use: A spray brake cleaner designed to remove oil, grease, brake fluid, brake pad material or dirt from motor vehicle brake mechanisms. **Manufacturer Information:** LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084 TEL: 1 770-243-8800 **Emergency Telephone Number:** 1-800-424-9300 Chemtrec; Outside U.S.: (703) 527-3887 FAX: 1 770-243-8899 Website: http://www.lpslabs.com

PLAIN LANGUAGE HAZARD SUMMARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably won't help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, don't hesitate to call us at 800/241-8334.

Worker Hazards

U-10 Brake Cleaner is a cleaning product designed to remove oil, grease, brake fluid, brake pad material or dirt from motor vehicle brake mechanisms. It contains acetone and aliphatic hydrocarbons that can be irritating to skin. We suggest you wear chemically resistant gloves and avoid extended exposure to unprotected skin. Don't get it in your eyes (it stings), or breath large amounts of the vapor, (it will dry out your nasal passages and if you breathe large amounts in poorly ventilated areas it can make you dizzy and even sick). Don't spray U-10 Brake Cleaner for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator or even a self-contained breathing apparatus may be necessary. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

Flammability

U-10 Brake Cleaner generates a "flame extension" when sprayed into an ignition source (flame, arc, etc.), but it is generally safe to use for most industrial applications. Store product away from heat sources and do not spray near live electrical equipment.

Disposal

If you spill U-10 Brake Cleaner notify the proper environmental or safety department at your company right away. If U-10 Brake Cleaner becomes contaminated with another substance and is rendered unusable for cleaning, the resulting mixture will fall under at least one hazardous classification. See section 13 for more details.



Revision 1

Revision Date: 8/19/08

Supercedes: None

Section 2 – Hazards identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Emergency Overview:

Aerosol: DANGER: Extremely Flammable. Eye irritant. Vapor harmful. Contents under pressure. Harmful or fatal if swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Potential Acute Health Effects:

- Eyes Irritating to eyes
- Skin Repeated exposure may cause skin dryness or cracking.
- **Inhalation:** Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.
- **Ingestion:** Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No OSHA: No ACGIH: No

Mutagenic Effects: None

Teratogenic Effects: None

Medical conditions aggravated by exposure:

Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms:

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

Section 3 – Compositon / Information on Ingredients					
Component	CASRN	Weight Percent			
Acetone	67-64-1	80 - 90%			
Methylcyclohexane	108-87-2	5 – 10%			
Carbon Dioxide	124-38-9	3 – 7%			



Revision 1

Revision Date: 8/19/08

Supercedes: None

Section 4 – First Aid Measures

- Eyes: Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low-pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.
 Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not use ointments. Seek medical attention persists.
 Inhalation: Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek
- **Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention immediately.

Section 5 – Fire Fighting Measures

Products of Combustion: Carbon monoxide and carbon dioxide.

Firefighting media: SMALL FIRE: Use DRY chemical powder.

medical attention immediately.

LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, auto ignition or explosions.

Sensitivity to Impact: None. Sensitivity to Static Discharge: None.

Protection Clothing (Fire): Firefighters must use full bunker gear including NIOSH-approved positive pressure selfcontained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

Special Remarks on Explosion Hazards: High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers. Aerosols may explode upon heating, spread fire and overcome sprinkler systems.

Section 6 – Accidental Release Measures

Containment Procedures	Contain and recover spilled liquid when possible.				
Clean-Up Procedures	Small Spill and Leak:	Eliminate ignition sources. Absorb with an inert material and dispose of properly.			
	Large Spill and Leak:	Eliminate ignition sources. Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal.			
Evacuation Procedures	Ventilate area of leak or spi	II. Keep unnecessary and unprotected people away.			
Special Procedures	Remove all sources of igniti cleanup.	on. Ventilate area. Wear appropriate protective equipment during			



Revision 1

Revision Date: 8/19/08

Supercedes: None

Section 7 – Handling and Storage

Handling: DO NOT spray into or around ignition sources. Do not allow material to come into contact with eyes or skin. Wear appropriate protective equipment during handling. Do not breathe vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

Precautions to be taken in handling and storage: *Store aerosols as Level 2 Aerosol (NFPA 30B).* Store all materials in dry, well-ventilated area. Avoid breathing vapors.

Section 8 – Exposure Controls / Personal Protection

Exposure Guidelines:

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH- TLV	ACGIH- STEL	NIOSH REL
Acetone	67-64-1	1000 ppm	Not Established	500 ppm	750 ppm	250 ppm TWA
Methylcyclohexane	108-87-2	500 ppm	Not Established	400 ppm	Not Established	400 ppm TWA
Carbon Dioxide	124-38-9	5000 ppm	30000 ppm	5000 ppm	30000 ppm	5000 ppm TWA 30000 ppm STEL

* Supplier Recommendation

Engineering Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines listed above.

Personal protective equipment

Eye protectionSafety glasses with side shields conforming to appropriate regulations. Eye wash fountain
and emergency shower facilities are recommended.

Hand protection Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, use chemical resistant gloves (i.e., neoprene, rubber latex, or butyl glove) conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.

Respiratory protectionTypical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e., organic vapor cartridge).

General Hygiene Wash throughly after handling. Have eye-wash facilities immediately available.

Considerations



Revision 1

Revision Date: 8/19/08

Supercedes: None

Section 9 – Physical and Chemical Properties

Appearance:	Liquid.	Color:	Colorless/water-white
Odor/Taste:	Ether-like/Fruity	Vapor Pressure:	1.98 mmHg
Solubility Description:	Soluble	Evaporation Rate:	< 1 (BuAc=1)
Boiling Point:	56°C(133°F)	Flash Point:	-20 °C(-4 °F)
Specific Gravity (Water=1):	0.75-0.77 at 20 °C	Flash Point Method:	Tag-Closed Cup.
Vapor Density (Air=1):	>2	Auto Ignition	465 °C (869 °F)
		Temperature:	285°C (545°F)
V.O.C. Content:	9.4% per CARB/OTC	Partition Coefficient (octanol/water):	>1
Flammable limits (estimated):	LOWER: 2.6% UPPER: 12.8%	Viscosity:	< 3 mm²/sec
pH:	Not applicable	Odor threshold	Not Established
Melting Point	Not Established	Volatiles:	100%
Decomposition Temperature	Not Established		

Section 10 – Chemical Stability and Reactivity

Product is stable under recommended storage conditions.
Keep away from heat and ignition sources.
Reactive or incompatible with oxidizing agents.
These products are carbon oxides (CO, CO2).
Will not occur.

Section 11 – Toxicological Information

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.

B: Component Analysis

Component	CASRN	LC-50	LD-50
Acetone	67-64-1	16000 ppm/rat/4H*	5800 mg/kg/oral/rat* 20000 mg/kg/dermal/rat*
Methylcyclohexane	108-87-2	15227 ppm/rabbit/1H	> 3200 mg/kg/oral/rat >86700 mg/kg/dermal/rabbit**
Carbon Dioxide	124-38-9	470000 ppm/rat/30min	Not Established

* Supplier Data

**RTECS LD₅₀ not reported, this is a Lethal Dose (LD) value.



Revision 1

Revision Date: 8/19/08

Supercedes: None

Section 12 – Ecological Information

Mobility:	Volatile. May partially absorb to sediment.	Persistence and degradability:	Partially biodegradable.
Bioaccumulative potential:	No bioaccumulation potential	Other adverse effects:	None known.

Ecotoxicology:

Effect on Organisms	Component	CASRN Test Specie		Species	Results
Acute Toxicity on Fishes	Acetone	67-64-1	96-hour LC_{50}	Alburnus alburnus	11000 mg/L
Aguta Taviaity an Danhaia	Acetone	67-64-1	48-hour EC ₅₀	Daphnia magna	12700 mg/L
Acute Toxicity on Daphnia	Methylcyclohexane 108-87-2 48-hour EC ₅₀		Daphnia magna	15 mmol/m ³	
Bacterial inhibition					
Growth inhibition of algae	No Data Available				
Bioaccumulation in fish					

Section 13 – Disposal Considerations

- Waste Status: Aerosol products, if depressurized and emptied to less than 2.5 cm of fluid contents are classified as non-hazardous waste under 40 CFR 261.7 (U.S.). If disposed of in its received form, this item carries waste code D001 and D003. (U.S.)
- **Disposal:** Waste must be disposed of in accordance with national, regional, provincial, and local environmental control regulations.
- **Note:** Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.



Revision 1

Revision Date: 8/19/08

Supercedes: None

Section 14 – Transportation Information

	Shipping Name:	ORM-D	UN Number:	NA
D.O.T. Ground	Hazard Class:	NA	Technical Name:	NA
	Subclass:	NA	Hazard Label:	ORM-D Already on box
	UN no:	1950	ADR Class:	2.1
Road/Rail -	Packing group:	NA	Classification code:	5F
ADR/RID :	Name and Description:	AEROSOLS, Flammable	Hazard ID no:	NA
	Labeling:	2.1		
	UN no:	1950	Class:	2.1
IMDG-IMO	Shipping Name:	AEROSOLS	Subsidiary Risk:	NA
	Packing Instructions:	NA	Packing group:	NA
	Marine pollutant:	NO	EmS:	F-D, S-U
	UN no:	1950	Class:	2.1
	Shipping Name:	AEROSOLS, Flammable	Subclass	NA
IATA-ICAO:	Packing instructions:	NA	Packing group:	NA
	Labeling:	Flammable Gas		

Section 15 – Regulatory Information

U.S. Federal Regulations

RCRA Hazardous Waste No.: D001, D003 (aerosols only)

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): None.

Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): No individual section 313 component is present at or above 1%

Section 112 Hazardous Air Pollutants (HAPs): None



Revision 1

Revision Date: 8/19/08

Supercedes: None

State Regulations

New Jersey RTK:

Acetone 67-64-1 • Methylcyclohexane 108-87-2 • Carbon Dioxide 124-38-9 • p-Amyl Acetate 628-63-7 • 1, 2-dimethylcyclopentane 2452-99-5

California: This product does <u>not</u> contain chemical(s) known to the State of California to cause cancer, birth defects or reproductive harm.


California and OTC States: This product conforms to consumer regulations.

International Regulations

Canadian Environmental Protection Act: All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System (WHMIS):

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.



Other Regulations

Montreal Protocol listed ingredients:NoStockholm Convention listed ingredients:NoRotterdam Convention listed ingredients:NoRoHS Compliant:Ye

None. None. None. Yes.

Section 16 • Other Information

	HMIS 19	996	HMIS III		NFPA
MSDS# 16220 Responsible Name:	Health:	1	Health:	[/]1	Flammability
Clea Johnson Regulatory Affairs Coordinator	Flammability:	3	Flammability:	3	3
	Reactivity	0	Physical Hazard:	2	Health 0 Reactivity

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea Johnson, Regulatory Affairs Coordinator LPS Laboratories, A division of Illinois Tool Works