

Specialty Paint & Protective Coatings

PRODUCT DATA SHEET

TOLUENE PTI-TOL SOLVENT

DESCRIPTION

Toluene is a low initial boiling point aromatic solvent. Toluene is clear, colorless, flammable liquid that is miscible with most common organic solvents. It is commonly used as a solvent and thinner in paints, lacquers, gums and resins. Also, Toluene has been found to work well as a cleaning, binding and release agent.

SOLVENT PROPERTIES & CHARACTERISTICS

Boiling Point	232°F - 233°F
Flash Point	45°F
Weight (lbs per gallon)	7.25 lbs
Color	Clear
Volatile Organic Compounds (VOC)	869 g/L
Specifications	TT-T-548, ASTM D843

SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

PRODUCT INFORMATION & DISCLAIMER

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.

PTI-ACT_PDS_Rev. 01 10/30/2012