

PRODUCT SAFETY INFORMATION SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

TRADE NAME: Self-Fusing Tape

PRODUCT NUMBERS COVERED:

A1###-B###-##	A3###-P###-##	LW###X##-##	9##-##X##-##	T4###-R###-##	99B##X###-##
A1###-R###-##	A3###-VG###-##	LW###C##-##	9##-##J##-##	T4###-B###-##	ARLON SFT
A1###-W###-##	A3###-X###-##	LW###H##-##	9##-##T##-##	RT920-##I##-##	HSLW###R##-##
A1###-X###-##	A3###-Y###-##	LW###I##-##	T1###-R###-##	RT920-##Y##-##	KTLW3015B5-P0
A2###-B###-##	A4###-B###-##	LW###T##-##	T1###-B###-##	RT920-##VR##-##	KTLW3015R5-P0
A3###-R###-##	LW###A##-##	LW###V##-##	T2###-R###-##	RT3020-B###-##	KTLW3015W5-P0
A3###-B###-##	LW###B##-##	LW###Y##-##	T2###-B###-##	RBLW###R##-##	KTLW3015T5-P0
A3###-I###-##	LW###R##-##	9##-##B##-##	T3###-R###-##	RBLW###X##-##	P3272-10R12##-##
A3###-J###-##	LW###W##-##	9##-##R##-##	T3###-B###-##	99B##R###-##	4811R###-##
48113R	99112T				

USE OF ARTICLE: Electrical and Mechanical Insulation

DATE ISSUED: 11/12/2015

COMPANY/UNDERTAKING Rogers Corporation

IDENTIFICATION: 1100 Governor Lead Rd

Bear, DE 19701 USA Phone: 01-302-834-2100 Fax: 01-302-834-4021

Email: msdsinfo@rogerscorporation.com

2. HAZARDS IDENTIFICATION

CLASSIFICATION OF THE MATERIAL: NE LABELING REQUIREMENTS: NE

EFFECTS OF OVEREXPOSURE: None are expected with normal handling. However, machining or grinding

may cause dusting. Processing material at temperatures exceeding

decomposition temperatures may release toxic fumes.

INHALATION: Dust generated during machining or grinding may cause respiratory

irritation.

EYE CONTACT:

SKIN CONTACT:

Dust may cause irritation.

Dust may cause irritation.

INGESTION: None known.

CHRONIC: NE

COMPOSITION/INFORMATION ON INGREDIENTS 3.

The materials are produced as an "article" as defined in 20 CFR 1910.1200 and REGULATION (EC) N° 1907/2006 is therefore exempt from the Hazard Communication Standard and REACH. Since this material does not release and will not result in exposure to a hazardous chemical under normal conditions of use, no Safety Data Sheet is required.

OSHA PEL Chemical Name CAS No. 15 mg/m³ 10043-35-3 Boric acid

FIRST-AID MEASURES 4.

INHALATION: Inhalation is unlikely in the supplied form. In the event move to fresh air.

Obtain medical attention if symptoms persist.

EYE CONTACT: Flush eyes with large amounts of water for 15 to 20 minutes. Obtain

medical attention if symptoms persist.

SKIN CONTACT: Immediately take off all contaminated clothing and flush area with water for

15 to 20 minutes. Obtain medical attention if symptoms persist.

INGESTION: Get medical attention.

FIRE-FIGHTING MEASURES 5.

FLASH POINT: NE °C (°F) Flammable LEL **UEL** NA NA

Limits:

NE °C (°F) **AUTOIGNITION TEMPERATURE:**

EXTINGUISHING MEDIA: X Water Spray X Foam Χ CO₂

X Dry Chemical Other

SPECIAL FIRE FIGHTING

PROCEDURES:

Decomposition in a fire may produce toxic fumes. Firefighters should be

equipped with self-contained breathing apparatus and turnout gear.

UNUSUAL FIRE AND EXPLOSION

HAZARDS:

Carbon monoxide, formaldehyde, silicon dioxide, and incompletely burned

carbon compounds.

6. **ACCIDENTAL RELEASE MEASURES**

PERSONAL PRECAUTIONS:

ENVIRONMENTAL PRECAUTIONS:

CLEANING METHODS:

Use personal protective equipment recommended in Section 8.

The material is not biodegradable.

Sweep or shovel into appropriate container for disposal.

HANDLING AND STORAGE 7.

HANDLING: Wear suitable protective equipment, refer to Section 8.

STORAGE: Store material in original packaging away from excess heat and

incompatible materials.

EXPOSURE CONTROLS/PERSONAL PROTECTION 8.

RESPIRATORY PROTECTION: None needed under normal conditions. If material is heated and odors are

noticeable and/or irritating a respirator meeting NIOSH requirements

should be used. A qualified individual should evaluate each situation.

VENTILATION

LOCAL: Recommended for all industrial operations. GENERAL: Recommended for all industrial operations.

PERSONAL PROTECTION

HAND: Wear suitable disposable gloves.

EYE: Safety glasses with side-shields are recommended in all industrial

operations.

SKIN: None required.

OTHER: Safety shower/eyewash in the area.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Silicone Rubber Tape (Various Colors)

ODOR: Characteristic Silicone

PHYSICAL STATE: Solid
BOILING POINT: NA °C (°F)
MELTING POINT: NE °C (°F)
FREEZING POINT: NA °C (°F)
FLASH POINT: NE °C (°F)
WATER SOLUBILITY: In-Soluble
VAPOR DENSITY: NA

VAPOR DENSITY: NA VAPOR PRESSURE: NA

SPECIFIC GRAVITY: 1.0-1.4 (Rubber Only)

AUTO-IGNITION TEMPERATURE: NA °C (°F)
DECOMPOSITION TEMPERATURE: NA °C (°F)

PH: NA FLAMMABILITY: NA

10. STABILITY AND REACTIVITY

STABLE X UNSTABLE

CONDITIONS TO AVOID: NE MATERIALS TO AVOID: NE

HAZARDOUS POLYMERIZATION: May Occur X Does Not Occur

HAZARDOUS DECOMPOSITION CO, formaldehyde, silicon dioxide, and traces of incompletely burned

PRODUCTS: carbon compounds.

11. TOXICOLOGICAL INFORMATION

CARCINOGENIC STATUS: NA

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NA

13. DISPOSAL CONSIDERATION

PHYSICAL/CHEMICAL PROPERTIES None

AFFECTING DISPOSAL:

ENVIRONMENTAL TOXICITY DATA: NA

WASTE DISPOSAL METHOD: Dispose of in accordance with applicable federal, state, provincial, and

local laws and regulations.

14. TRANSPORT INFORMATION

UN NUMBER:
UN PROPER SHIPPING NAME:
HAZARD CLASS (ES):
PACKING GROUP:
Not Regulated
Not Regulated
Not Regulated

ENVIRONMENTAL HAZARDS: NE

15. REGULATORY INFORMATION

INTERNATIONAL REGULATIONS:

Canadian (DSL/NDSL):

Article – exempt
Australian (ACIS):

Korea (KECI):

Japan (ENCS, MITI):

China (IECSC):

Article – exempt
Article – exempt
Article – exempt
Article – exempt

EU Directive 2011/65/EC (RoHS): Product is in compliance with the European Directive 2011/65/EC on

Restriction on Hazardous Substances and the Chinese Administration Measure on the Control of Pollution Caused by Electronic Information.

EU REACH SVHC: Product contains 0.1-3.0 wt. % boric acid a SVHC. Boric acid is a

suspected human reproductive toxicant and is absorbed mainly through ingestion and inhalation. Ingestion and inhalation of this chemical substance should be avoided. Dermal absorption of boric acid through intact skin is negligible and personal protective equipment should be used. Wash thoroughly after handling material prior to eating, drinking.

or smoking.

TSCA All materials are listed or exempt from TSCA listing.

(Toxic Substances Control Act):

CERCLA NA

(Comprehensive Emergency Response,

Compensation, and Liability Act):

SARA TITLE III NA

(Superfund Amendments and

Reauthorization Act):

311/312 HAZARD CATEGORIES: None

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the

Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS# CHEMICAL NAME PERCENT BY WEIGHT
NA NA

16. OTHER INFORMATION

NA = Not Applicable FILE: 99403 Self-Fusing Tape PSIS 11122015

NE = Not Established

NC = Not Classified PREPARED BY: Jianhua Zou REVIEWED BY: Michal Werbecki

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF. ROGERS CORPORATION ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.