


ALLOY/STRUCTURAL — MACHINE SCREWS

NAS600 - NAS603 MACHINE SCREWS



Thread	Length	Part No.	Price Ea.
4-40	.188	NAS600-3P	\$0.09
	.250	NAS600-4P	\$0.08
	.312	NAS600-5P	\$0.09
	.375	NAS600-6P	\$0.09
	.438	NAS600-7P	\$0.11
	.500	NAS600-8P	\$0.07
6-32	.188	NAS601-3P	\$0.12
	.250	NAS601-4P	\$0.07
	.312	NAS601-5P	\$0.08
	.375	NAS601-6P	\$0.09
	.438	NAS601-7P	\$0.08
	.500	NAS601-8P	\$0.12
8-32	.562	NAS601-9P	\$0.14
	.625	NAS601-10P	\$0.14
	.750	NAS601-12P	\$0.14
	.188	NAS602-3P	\$0.15
	.250	NAS602-4P	\$0.11
	.312	NAS602-5P	\$0.13
	.375	NAS602-6P	\$0.14
	.438	NAS602-7P	\$0.11
	.500	NAS602-8P	\$0.15
	.562	NAS602-9P	\$0.14
	.625	NAS602-10P	\$0.12
	.688	NAS602-11P	\$0.13
.750	NAS602-12P	\$0.18	
.813	NAS602-13P	\$0.14	
.875	NAS602-14P	\$0.15	
.1.00	NAS602-16P	\$0.15	
10-32	.250	NAS603-4P	\$0.17
	.312	NAS603-5P	\$0.14
	.375	NAS603-6P	\$0.14
	.438	NAS603-7P	\$0.18
	.500	NAS603-8P	\$0.20
	.562	NAS603-9P	\$0.21
	.625	NAS603-10P	\$0.21
	.688	NAS603-11P	\$0.19
	.750	NAS603-12P	\$0.23
	.813	NAS603-13P	\$0.17
	.875	NAS603-14P	\$0.28
	.938	NAS603-15P	\$0.16
1.00	NAS603-16P	\$0.25	
1.125	NAS603-18P	\$0.23	
1.25	NAS603-20P	\$0.39	




- Phillips Pan Head
- Alloy Steel (8740)
- Finish - Cadmium per QQ-P-416
- Tensile -160,000 - 180,000 PSI

NAS1202 / NAS1203 FLUSH HEAD SCREWS

- Phillips 100° Flat Head • Tensile - 160,000 - 180,000 PSI
- Alloy Steel Per MIL-S-6049 • Finish - Cadmium per QQ-P-416, Type II



Thread	Grip	Length	Part No.	Price Ea.
8-32	.125	.401	NAS1202-2	\$0.14
	.188	.464	NAS1202-3	\$0.16
	.250	.526	NAS1202-4	\$0.13
	.312	.588	NAS1202-5	\$0.15
	.375	.651	NAS1202-6	\$0.17
10-32	.125	.401	NAS1203-2	\$0.23
	.188	.464	NAS1203-3	\$0.18
	.250	.526	NAS1203-4	\$0.20
	.312	.588	NAS1203-5	\$0.17
	.375	.651	NAS1203-6	\$0.18
	.438	.714	NAS1203-7	\$0.22
	.500	.776	NAS1203-8	\$0.18




MS51959 MACHINE SCREWS

- Phillips 82° Flat Head • Stainless Steel

Thread	Length	Part No.	Each	Thread	Length	Part No.	Each	
2-56	.188	MS51959-2	\$0.04	6-32	.312	MS51959-27	\$0.09	
	.250	MS51959-3	\$0.04			.375	MS51959-28	\$0.08
	.312	MS51959-4	\$0.04			.438	MS51959-29	\$0.07
	.375	MS51959-5	\$0.05			.500	MS51959-30	\$0.07
	.250	MS51959-13	\$0.04			.625	MS51959-31	\$0.07
4-40	.312	MS51959-14	\$0.07	8-32	.375	MS51959-43	\$0.09	
	.375	MS51959-15	\$0.07			.438	MS51959-44	\$0.09
	.438	MS51959-16	\$0.07			.500	MS51959-45	\$0.09
	.500	MS51959-17	\$0.07			.625	MS51959-46	\$0.09
					.750	MS51959-47	\$0.11	


NAS1096 HEX HEAD SCREWS



- Phillips Hex Head
- Alloy Steel per MIL-S-6049
- Finish - Cadmium per QQ-P-416 Type II
- Tensile - 125,000-145,000 PSI

Thread	Length	Part No.	Price Ea.
6-32	.375	NAS1096-1-6	\$0.14
	.438	NAS1096-1-7	\$0.11
	.500	NAS1096-1-8	\$0.19
	.562	NAS1096-1-9	\$0.16
	.625	NAS1096-1-10	\$0.15
	.750	NAS1096-1-12	\$0.18
8-32	.312	NAS1096-2-5	\$0.10
	.375	NAS1096-2-6	\$0.15
	.438	NAS1096-2-7	\$0.13
	.500	NAS1096-2-8	\$0.13
	.562	NAS1096-2-9	\$0.18
	.625	NAS1096-2-10	\$0.17
10-32	.750	NAS1096-2-12	\$0.17
	.312	NAS1096-3-5	\$0.12
	.375	NAS1096-3-6	\$0.18
	.438	NAS1096-3-7	\$0.18
	.500	NAS1096-3-8	\$0.17
	.562	NAS1096-3-9	\$0.16
	.625	NAS1096-3-10	\$0.18
	.750	NAS1096-3-12	\$0.23
	.875	NAS1096-3-14	\$0.26
	1.00	NAS1096-3-16	\$0.28
	1.25	NAS1096-3-20	\$0.38

NAS1801 HEX HEAD SCREWS



- Phillips Hex Head
- Alloy Steel Per MIL-S-6049
- Finish - Cad Plate per QQ-P-416, Type II
- Tensile - 160,000-185,000 PSI

Thread	Length	Part No.	Price Ea.
8-32	.250	NAS1801-08-4	\$0.19
	.312	NAS1801-08-5	\$0.17
	.375	NAS1801-08-6	\$0.16
	.438	NAS1801-08-7	\$0.14
	.500	NAS1801-08-8	\$0.19
	.562	NAS1801-08-9	\$0.22
	.625	NAS1801-08-10	\$0.18
	.750	NAS1801-08-12	\$0.22
	.875	NAS1801-08-14	\$0.22
	1.00	NAS1801-08-16	\$0.21
	1.125	NAS1801-08-18	\$0.21
	1.25	NAS1801-08-20	\$0.21
10-32	1.375	NAS1801-08-22	\$0.45
	.312	NAS1801-3-5	\$0.16
	.375	NAS1801-3-6	\$0.19
	.438	NAS1801-3-7	\$0.19
	.500	NAS1801-3-8	\$0.21
	.562	NAS1801-3-9	\$0.35
	.625	NAS1801-3-10	\$0.24
	.750	NAS1801-3-12	\$0.26
	.875	NAS1801-3-14	\$0.24
	1.00	NAS1801-3-16	\$0.34
	1.125	NAS1801-3-18	\$0.36
	1.25	NAS1801-3-20	\$0.28
1.375	NAS1801-3-22	\$0.48	
1.50	NAS1801-3-24	\$0.51	

NAS623 PAN HEAD SCREWS



- Phillips Pan Head • Alloy Steel per MIL-S-6049 • Finish - Cad Plate per QQ-P-416, Type II • Tensile - 160,000-185,000 PSI

Thread	Length	Part No.	Each	Thread	Length	Part No.	Each	
8-32	.338	NAS623-2-1	\$0.14	10-32	.588	NAS623-3-5	\$0.17	
	.401	NAS623-2-2	\$0.15			.651	NAS623-3-6	\$0.18
	.464	NAS623-2-3	\$0.16			.714	NAS623-3-7	\$0.22
	.526	NAS623-2-4	\$0.14			.776	NAS623-3-8	\$0.19
	.588	NAS623-2-5	\$0.19			.838	NAS623-3-9	\$0.22
	.651	NAS623-2-6	\$0.21			.901	NAS623-3-10	\$0.17
	.714	NAS623-2-7	\$0.19			.964	NAS623-3-11	\$0.19
	.776	NAS623-2-8	\$0.21			1.026	NAS623-3-12	\$0.21
	.838	NAS623-2-9	\$0.20			1.088	NAS623-3-13	\$0.18
	.901	NAS623-2-10	\$0.17			1.151	NAS623-3-14	\$0.21
	.964	NAS623-2-11	\$0.21			1.214	NAS623-3-15	\$0.24
	1.026	NAS623-2-12	\$0.20			1.276	NAS623-3-16	\$0.21
10-32	.401	NAS623-3-2	\$0.16		1.338	NAS623-3-17	\$0.24	
	.464	NAS623-3-3	\$0.18		1.401	NAS623-3-18	\$0.32	
	.526	NAS623-3-4	\$0.15					

HA