

ECOPOXY UVPOXY

Ecopoxy UVPoxy Kit is high performance two part system that is commonly used for table tops, bars, wood finishes, see-through clear casting, art work, layup, and other applications requiring a clear, strong coating. It cures to a crystal clear, high build, long lasting, glass-like finish, and will not blush or sweat under high humidity conditions. UVpoxy is designed to resist yellowing caused by the sun and other ultra violet light sources.

Features: • Crystal Clear - Cures to a clear, glass-like finish · Low Odour - It's safe to use

indoors, no ventilation or respiration required • UV Stable - Won't fade or yellow, your finishes will last forever! • User Friendly - Mixes at a 1:1 mix ratio, very easy to calculate amounts needed • Low Drip - Thicker viscosity ensures it does not drip onto other areas · Self-Leveling - Selflevels perfectly, making for a nice even finish every time!

Specifications: • Color: Clear (Visual) • Mix Ratio: 1:1 • Pot Life: 25-30 Minutes

| Description (Metric / Approx. US) | Size | Part No. | Price |
|--------------------------------------|---------------|----------|-------|
| EcoPoxy UVPoxy Kit | 500 mL / 1 Pt | 09-04095 | |
| EcoPoxy UVPoxy Kit | 1 L / 1 Qt. | 09-04096 | |
| EcoPoxy UVPoxy Kit | 4 L / 1 Gal. | 09-04098 | |



ECOPOXY FAST KIT - 1.6 GAL

Our Fast Kit is most commonly used as an adhesive or in an injection box for pultrusion. It has a pot time of just 2-3 minutes, and features a highstrength, waterproof bond to a variety of materials including wood, fiberglass, metal, glass, tile, and more.

Specifications: • Color: Yellow (Visual) · Mix Ratio: 2:1 · Pot Life: 2.5-3 Minutes.

P/N 09-04116----



POLYESTER GEL COATS

These polyester gel coats can be used as the surface of fiberglass parts layed up in molds or used in the repair of gel coat surfaces on fiberglass parts. On surface repairs, the gel coat must be sealed to fully cure. PVA can be used to seal the gel coat.

| Color | Part No. | Pint Price | Part No. | Quart Price | Part No. | Gallon Price |
|-----------|----------|---------------|----------|----------------|----------|-----------------|
| Black | 09-01668 | | 09-01666 | | 09-01667 | |
| White | 09-01669 | | 09-01664 | | 09-01665 | |
| Dark Blue | 09-01670 | | 09-01671 | | 09-01672 | |
| Red | 09-01673 | | 09-01674 | | 09-01675 | |
| Clear | 09-02159 | | 09-02160 | | 09-02161 | |



V-NOTCHED ECOPOXY SPREADER

The perfect tool for evenly spreading EcoPoxy on large, flat surfaces. This tool gives you 3 V-notched spreading scraping and cleaning.

P/N 09-05355----V-notched spreading options and a flat side for



ECOPOXY LIQUID PLASTIC KIT

The Liquid Plastic kit cures to a clear, UV resistant, plastic-like finish that resists scratching and yellowing. This product will not blush or sweat under high humidity conditions. EcoPoxy® is a Plant based, 100% solid, waterproof, non-toxic, non-solvent, non-conductive, epoxy system that is Certified "Green"...P/N 09-04567......



ECOPOXY ECOTROWEL MULTI-PACKS

EcoTrowel is a high performance epoxy filler and profiling product formulated for surface repair and preparation. It is easy to mix and spread, and has a peanut-butter like consistency (contains no peanuts!). EcoTrowel is lightweight and suitable for an infinite variety of composite, architectural, industrial and art-related

applications. It can be applied to wood, concrete - even canvas - to a thickness of 1/2" without sagging or slumping. It can be easily sanded, shaped, drilled, tapped, machined, routered & remains durable for life.

| 20y | F/N 09-03333 | |
|------|--------------|--|
| 100g | P/N 09-05354 | |

ECOPOXY GLOPOXY KITS



GloPoxy is a glow-in-the-dark epoxy made with high-grade photo lumines-cent ingredients to maximize glow brightness and duration. The formula absorbs bright light as energy and releases the absorbed energy when placed in the dark. This charge cycle can be performed endlessly and with any light source. GloPoxy is formu-

lated to glow-in-the-dark for hours and contains no fillers or impurities to interfere with the glow. GloPoxy is durable, UV stable, and chemical, water & abrasion resistant. It can be used indoor and outdoor, and can be applied to virtually any surface. It's a perfect solution for both safety and novelty applications.

BlueP/N 09-05348---

ECOPOXY PIGMENT COLOR SETS



Add some color to your epoxies. These are used to tint epoxy resins used as coatings, paints, gelcoats, laminating, casting or self-leveling resins. EcoPoxy epoxy concentrated pigment consist of pigments suspended in epoxy resin which allows them to blend thoroughly into epoxy resins to make very uniform colors. They are used to tint epoxy resins used as coatings, paints, gelcoats, laminating, casting or self-leveling resins. The high tinting properties enable the use of little quantities of pigment. The quantity to be used depends on the color chosen as some colors cover better than other (yellows for example need higher quantities than other colors). ECOPOXY color pigments mix easily.

| 6Um | P/IN | 09-05349 | |
|-------|------|----------|--|
| 120ml | P/N | 09-04718 | |
| 240ml | P/N | 09-05351 | |