# DUCTING

# AIRCRAFT FLEXIBLE DUCTING (SOLD IN PRE-CUT LENGTHS)

Dash No.	Inside Diameter	CAT TYPE		SCAT TYPE		CEET TYPE		SCEET TYPE	
		Part No.	Price/Foot	Part No.	Price/Foot	Part No.	Price/Foot	Part No.	Price/Foot
-2A	5/8"	05-29801		05-29901		05-30501		05-30601	
-3	3/4"	05-29802		05-29902		05-30502		05-30602	
-3A	7/8"	05-29803		05-29903		05-30503		05-30603	
-4	1"	05-29804		05-29904		05-30504		05-30604	
-5	1-1/4"	05-29805		05-29905		05-30505		05-30605	
-6	1-1/2"	05-29806		05-29906		05-30506		05-30606	
-7	1-3/4"	05-29807		05-29907		05-30507		05-30607	
-8	2"	05-29808		05-29908		05-30508		05-30608	
-9	2-1/4"	05-29809		05-29909		05-30509		05-30609	
-10	2-1/2"	05-29810		05-29910		05-30510		05-30610	
-11	2-3/4"	05-29811		05-29911		05-30511		05-30611	
-12	3"	05-29812		05-29912		05-30512		05-30612	
-13	3-1/4"	05-29813		05-29913		05-30513		05-30613	
-14	3-1/2"	05-29814		05-29914		05-30514		05-30614	
-15	3-3/4"	05-29815		05-29915		05-30515		05-30615	
-16	4"	05-29816		05-29916		05-30516		05-30616	
-18	4-1/2"	05-29818		05-29918		05-30518		05-30618	
20	5"	05-29820		05-29920		05-30520		05-30620	
24	6"	05-29824		05-29924		05-30524		05-30624	

Available in 3', 5', 8' and 13' pre-cut lengths. Use basic p/n and add -3, -5, -8, or -13 to complete the part number.

Example: A 3 ft. length of Cat-8 is p/n 05-29808-3.

# THERMOID AERODUCT DUCTING (SOLD IN FULL LENGTH)



"CAT" - "CAT" type flexible hot or cold air ducting is extremely lightweight and highly flexible. Short lengths can be joined together to form a continuous length. Made of a single ply black neopreneimpregnated fiberglass with a spiral copper coated steel wire inside and wrapped with fiberglass cord on the outside. Suitable for conveying fumes and air a temperatures from -65° to over 350°F. Not recommended for handling liquids or highly abrasive materials, or for negative pressure applications.

"SCAT" - "SCAT" type ducting has the same type construction as "CAT" except with red silicone rubber impregnation. For use in conducting extremely cold or hot air with temperatures from -65° to over 550°F. Not recommended for negative pressure applications.

"CEET" - "CEET" type ducting has two plies of neoprene-impregnated fiberglass, similar to CAT except wire between plies. For use in hot or cold air applications and for conveying fumes at temperatures ranging from -65° to over 350°F. Not recommended for handling liquids or highly abrasive materials, or for negative pressure applications.

"SCEET" - "SCEET" type ducting has two plies of silicone rubber-impregnated fiberglass, similar to SCAT except wire between plies. Ideal for use in conducting extremely cold or hot air at temperatures from -80° to over 550°F, and for conveying fumes. Not reccomended for handling liquids or highly abrasive materials, or for negative pressure applications.

Dash No.	Inside Diameter	CAT		SCAT		CEET		SCEET	
		Part Number	Price Per 10 Foot	Part Number	Price Per 11 Foot	Part Number	Price Per 10 Foot	Part Number	Price Per 11 Foot
-2A	5/8 *	05-11867	*	05-11864	*	05-11888	*	05-11871	*
-3	3/4	05-11878		05-11869		05-11879		05-11874	
-4	1	05-11862		05-11851		05-11875		05-11855	
-5	1-1/4	05-11863		05-11856		05-12455		05-11861	
-6	1-1/2	05-12437		05-11852		05-12443		05-11857	
-7	1-3/4	05-12447		05-12439		05-12441			
-8	2	05-12433		05-11848		05-12436		05-11853	
-9	2-1/4	05-12449		05-11859		05-12445		05-11876	
-10	2-1/2	05-12434		05-11850		05-12446		05-11858	
-11	2-3/4	05-12450		05-11865		05-12452		05-11877	
-12	3	05-12438		05-11849		05-12435		05-11854	
-13	3-1/4	05-12459		05-11868		05-12453		05-11881	
-14	3-1/2	05-12458		05-11872		05-12456		05-11880	
-15	3-3/4	05-12463		05-11887		05-12462		05-11889	
-16	4	05-12442		05-11860		05-12440		05-11866	
-18	4-1/2	05-12457		05-11882		05-12451		05-11886	
-20	5	05-12448		05-11873		05-12461		05-11883	
-24	6	05-12454		05-11885		05-12460		05-11884	

### \* 5/8 DIAMETER PIECES ONLY COME IN 5 FOOT LENGTHS.



## **ALUMINUM FLANGES FOR DUCTING**

Simplify installation of cabin, carb. heat, cabin vent lines. Aluminum flange may be welded or riveted in place. Slip ducting over outlet and secure with clamp.

Ducting Size	Part No.	Price	Ducting Size	Part No.	Price	Ducting Size	Part No.	Price
1"	10350-4		1-3/4"	10350-7		2-1/2"	10350-10	
1-1/4"	10350-5		2	10350-8		2-3/4"	10350-11	
1-1/2"	10350-6		2-1/4"	10350-9		3"	10350-12	

# 2 INCH ALUMINUM SCAT TUBE INLET

This 2" Scat Tube Inlet is fabricated from 6061 Aluminum with per-drilled 3/32 rivet holes, ready to rivet to baffling. P/N 05-12782.....