

AXLES

HOMEBUILDERS MAIN GEAR AXLES ACS AXLES - BOLT-ON TYPE



500X5 AXLE - Machined from 2024T3 aluminum. Gold anodized per specification MIL-A-8625C, Type II for improved corrosion resistance. Length 5-3/4". Mounting bolt pattern is four equally spaced 1/4" dia. holes on 1-15/16" dia. bolt circle. Thread size: 1-1/4 x 16.

P/N 11701 Ea.

500X5 AXLE - For 199-152 heavy duty discs (as used in Cozy). Same as #11701 axles above except 6" long and without undercut between bearings.

P/N 11701-2 Ea.

SPACERS FOR 500 X 5 AXLE - 2 required per axle when used with Cleveland wheels. Not required on 600x6 size.

P/N 11716 Ea.

EXTRA WIDE SPACER FOR 500X5 AXLE - 7/16" wide as used on 199-152 heavy duty discs. 1 required per axle with P/N 11716 (Use Axle # 11701-2)

P/N 11716-2 Ea.

ACS AXLES - WELD-ON TYPE

500 X 5 AXLE - For use on welded type gear. Fabricated from 1-1/4" O.D. x .120 wall 4130N steel tubing. Precision ground for proper bearing fit. One end threaded 1-1/4 x 12 for round axle nut. 12" long.

P/N 11703-1 Ea.

600 X 6 AXLE - For use on welded type gear. Fabricated from 1-1/2" O.D. x .120 wall 4130N steel tubing. Precision ground for proper bearing fit. One end threaded 1-1/2 x 16 for round axle nut. 12" long.

P/N 11704-1 Ea.



06-11800
06-11900

AXLE NUTS

Castle type nuts manufactured to MIL Specification MS21025 using 4140 steel. Mild steel nuts are not acceptable for use on certificated aircraft. 1-1/4" dia. nuts for 500 x 5 axles, 1-1/2" dia. nuts for 600 x 6 axles.

Nut Type		Thread	Axle Type	Part No.	Price
Matco	Castle	5/8-18	Matco	06-11815	---
---	Castle	1-1/4-16	Cessna	06-11800	---
---	Castle	1-1/2-16	Cessna	06-11900	---
ACS	Round	1-1/4-12	Piper	11725	---
ACS	Round	1-1/2-16	Piper	11726	---
Grove	Round	1-1/4-12	Piper	06-00937	---

TAPER SHIMS

For wheel alignment. Ideal setting is zero toe-in and zero camber at normal operating weight. Shims may be rotated to any one of four positions to obtain desired result.



0441157-1

Axle Size	Shim Part No.	Approx. correction value		Price Each
		Camber	Toe-In	
500x5	0441157-1	1/2°	0.06"	---
	0441157-3	1°	0.12"	---
	0441157-2	2°	0.006"	---
600x6	0441139-5	1/2°	0.12"	---
	0441139-6	1°	0.20-0.25"	---
	0541111-2	2-1/2°	0.10-0.25"	---

AXLE WITH WOODRUFF KEY



Axle 5/8" x 8" with Woodruff Key (Cotter Pin hole) P/N 06-01004 Ea.

GROVE AXLES

For 500X5 Wheels with Wheel Pant Stub
• Diameter: 1.25" • Material: Solid 2024-T3 aluminum w/anodized finish • Hole Pattern: 1-15/16" bolt circle; 1/4" dia. holes. Requires (2) P/N5710 spacers per axle.

P/N 06-00601 Ea.



For 600X6 Wheels with Wheel Pant Stub
• Diameter: 1.5" • Material: Solid 2024-T3 aluminum w/anodized finish • Hole Pattern: 2.25" bolt circle; (2) 2-15/16" dia. bolt holes & (2) 2-3/8" dia. bolt holes.

P/N 06-00602 Ea.



GROVE AXLE SPACER 5712

I.D.: 1.25", O.D.: 1.438", Thickness: 0.360", Used with 5015 axle, 1 (one) required per axle.

P/N 06-01504 Ea.



GROVE AXLE SPACER 5710

I.D.: 1-1/4" • O.D.: 1-3/4", Thickness: 1/4", Used with 500x5 axle, 2 required per axle P/N 06-00852 Ea.



GROVE ALUMINUM WHEEL PANT AXLE NUTS

Model	Axle	Thread	Part No.	Price
5512	500x5	1-1/4x16	06-01677	---
5513	600x6	1-1/2x16	06-01678	---
--	400x4	3/4x16	06-01742	---



CESSNA MAIN GEAR AXLE

For use on flat spring landing gear, Cessna models 180, 182, 185 and 206. It is highly recommended to replace aluminum axles with these much stronger steel axles when operating on rough conditions, with larger wheels or on skis. FAA-PMA approved.

Steel P/N 05-00481 Ea.
Titanium P/N 05-12478 Ea.



TLGW TITANIUM MAIN LANDING GEAR

Landing Gear Works has refined and perfected the titanium main spring landing gear for Skywagon 180 and 185 aircraft. Titanium main landing gear does not fatigue or lose its spring like standard steel main landing gear! Heavy Duty: P/N XP0741001K (weight: 23lbs per leg) Light Duty: P/N XP0741001KLD (weight: 21lbs per leg) Includes STC Paperwork!



Description	Part No.	Price
The Landing Gear Works Main Landing Gear Set Titanium XP0741001K	05-32376	---
The Landing Gear Works Main Landing Gear Set Ld Titanium XP0741001Kld	05-32377	---

SEE OUR WEBSITE FOR APPLICABLE AIRCRAFT LIST
SEE OUR WEBSITE FOR COMPLETE TLGW PRODUCT LIST

GROVE HOMEBUILT AIRCRAFT LANDING GEAR

These custom landing gear are fabricated from aircraft grade 2024T3 aluminum. After cutting and milling, they are annealed to "O" condition for bending, and then heat-treated to "T6" condition for exceptional strength and durability. Top quality landing gear at exceptional pricing.

Aircraft Type	Part No.	Price
KITFOX - Mod 3&4 TD	06-04025	---
PITTS - S1	06-03915	---
S1-11B SuperStinker	06-04035	---
Baby Lakes	06-04070	---
VP1 - 1100B Free Standing No Cables	06-04040	---
Zenair CH701	06-00058	---

NOTE: Request landing gear layout sheet when placing order or quotation Request for custom landing gear to verify correct gear for application.

NOTE: ALL GROVE AIRCRAFT LANDING GEAR IS
NON-CANCELLABLE / NON-RETURNABLE.