

# BENDIX-KING

## KING KSN 770 INTEGRATED SAFETY NAVIGATOR



An affordable, WAAS-Enabled, Integrated MFD with a flexible hybrid user interface. Features: • High-res VGA display (5.7" diagonal, 5.25" high). • Hybrid user interface • Electronic charts and maps. • WAAS GPS enroute and approach navigation system. • \*\*TCAS and Radar, \*\*TAWS and Stormscope. • XM WX interface. • 10W COM with

optional high-power 16W COM.-Digital radio core • Analog and digital inputs/outputs. • EPIC/APEX FMS Core. • Simple to use • Affordable pricing • Enhanced ground proximity warning system (option). • Nav/Com (10W Com with 16W option) .....P/N 11-12340 ..... ---

## SILVER CROWN KX-165A NAV/COM SYSTEM



Large, self-dimming, microprocessor-controlled gas discharge readouts and solid-state electronic tuning provide fast, accurate selection of all 200 Nav & 760 Comm frequencies. On the COMM

side, the KX165 system gives you 10W minimum transmitter power for maximum range and clarity. And on the NAV side, the KX165's useful 'Radial' feature offers you an instant readout of the radial you're on (from the 'active' VORTAC station), digitally displayed in the 'standby' NAV frequency window. The KX-165A is TSO'd and offers 32 channels of com frequency memory, an additional CDI mode. The GPS "Quick Tune" feature allows the pilot to select and remotely tune the standby com & nav freq. from the KLN94 GPS 28V

25 khz.....P/N 11-00644 ..... ---

8.33 khz.....P/N 11-16032 ..... ---

## CROWN KX 125 DIGITAL NAV/COM



The KX-125 is ideal as a replacement radio, a primary system for homebuilts or a very affordable back-up. COMM section provides 760 frequencies, 'flip-flop' frequency selection, a built-in

audio amplifier with sidetone and audio leveling, direct tuning, stuck-microphone alert, and even remote transfer of both COMM and NAV frequencies. Its separate NAV section offers 200 frequencies, including localizer. Includes unit, install kit, nd manual.

KX-125 Unit Only.....P/N 11-02585 ..... ---



## CROWN KI SERIES INDICATORS

The KI203, KI208, KI204, & KI209 indicators feature an internal VOR/ LOC converter and are compatible with the KX155 transceiver. The KI203 & KI204 have rectilinear meter movement, while the KI208 & KI209 feature pivot needle action. The KI206 has rectilinear meter movement and works with the KX165 & KNS80. The KI209 includes GPS interface capability. Size: 3.125" x 8"D; Weight: 1.5lbs.

KI 203 NAV Indicator.....P/N 11-03407 ..... ---

KI 204GS Indicator.....P/N 11-03408 ..... ---

KI 209A GS Indicator.....P/N 11-03409 ..... ---

KI 208A 14/28V with install .....P/N 11-07599 ..... ---

KI 209 GS Indicator.....P/N 11-00878 ..... ---

KI 206 GS Indicator.....P/N 11-04209 ..... ---

## BENDIX/KING XVUE TOUCH FLIGHT DECK SYSTEM



The xVue Touch is centered around an industry leading 10.1" display with a near 4K resolution and 1000 nits of luminescence. This stunning and intuitive interface places all critical functions just two touches away on its anti-glare, anti-smudge, and anti-scratch display. With cutting edge 97% touch accuracy, it is easy to control all of the functionality that comes standard with the system, including SmartView Synthetic Vision, Vertical Situation Display, and ADS-B In weather and traffic display.

These features, within a variety of possible screen configurations, lead to improved situational awareness and safety.

P/N 11-16286 ..... ---

## BENDIX/KING KT 74 TRANSPONDER



The KT 74 transponder from Bendix/King is the easiest upgrade to the popular KT 76A/C and KT 78A models, with a 'plug and go' capacity. And it's ADS-B compliant, therefore meeting all 2020 requirements. It is low-cost, easy to install and fits into your existing panel. Suiting your needs now and in the future.

KT 74 ADVANTAGE: • Retrofit - 'plug and play' installation • Low-cost solution that will offset future costs • Low power consumption • ETSO and TSO approved Mode S • Accurate readings with updates every few seconds • More efficient routing and better situational awareness • Meets ADS-B 2020 requirements" .....P/N 11-12038 ..... ---

## CROWN KY 96A & KY 97A COM



Bendix/ King has designed the KY 96A and KY 97A to operate on 760 frequencies from 118.00 MHz to 136.975 MHz. You can switch between active and standby frequencies. Simply tune the desired frequency into the standby window ("STBY") while monitoring the "USE" channel-when the time is right, simply push the frequency transfer button to transfer the standby frequency into the active window. A remote switch may be installed as an additional means of providing the "flip-flop" function. Up to nine channels can be easily programmed by the pilot into the memory of the KY 96A or KY 97A. The KY 96A & KY 97A remember displayed frequencies and stored frequencies without batteries or external hookup during power shutdown or in the event of a power interruption and have an easy-to-read, illuminated LCD display.

KY 96A (28V) .....P/N 11-03411 ..... ---

### Accessories

King Install Manual KY96A/97A .....P/N 11-18005 ..... ---

## CROWN SERIES KT-76A MODE C TRANSPONDER



The KT76A is a panelmount, class 1-A transponder and provides maximum performance at any altitude up to 35,000 ft. A compact unit with Large Scale Integrated (LSI) circuitry, reducing both weight and power requirements. All Mode A & Mode C transponders perform the same functions: replying to radar interrogations, providing Air Traffic Control (ATC) with positive identification, and showing your ground speed on the Controller's radar monitor. If you have an encoding altimeter or blind encoder, the transponder will transmit your altitude as well.

KT76A 06 14V (Transponder) .....P/N 11-02438 ..... ---

28V Dropping Resistor .....P/N 11-00913 ..... ---

Replacement Bulb Container .....P/N 11-00522 ..... ---

14V Without Harness .....P/N 11-02440 ..... ---

28V Without Harness .....P/N 11-02441 ..... ---

## KING SILVER CROWN KT 76C MODE C TRANSPONDER



The unit features a bright, gas plasma display that shows the selected transponder code and, in a new feature, the encoder altitude output. The KT 76C will fit directly into the existing location of a KT 76A. However, in 28V installations the existing dropping resistor must be bypassed. Unit operates from 11-33VDC. Available with or without antenna.

Without KA 61 Antenna.....P/N 11-03413 ..... ---

With KA 61 Antenna Without Harness .....P/N 11-03414 ..... ---

Honeywell Crown Series can only be sold over the counter. Silver Crown series can only be sold to experimental aircraft (must verify) with harness. For certified aircraft, it must be installed by a Honeywell Dealer. Please call 1-800-826-3160 for partner shop location for certified installs. (price of installation not included)

### BENDIX KING UPGRADES

See [www.aircraftspruce.com](http://www.aircraftspruce.com) for details on upgrading your current Bendix King Avionics.

AV