

ADHESIVES - GLUES

WP



CASCOPHEN

A Resorcinol Formaldehyde Adhesive capable of curing at room temperature and providing strong, durable, waterproof bonds. Comes in two parts, a liquid resin (part A) and a powdered catalyst (part B). The liquid resin is an alcohol-water solution of a partially condensed resorcinol-formaldehyde resin containing a suitable reinforcing cellulosic filler. The hardener is a tan powder formulated from paraformaldehyde and a suitable cellulosic filler. Produces a cured glue line which is resistant to fresh water or salt water, most acids and organic solvents, and lubricating oils and greases. Being thermoset, the bond is resistant to elevated temps. and conversely, no loss in bond strength occurs at temperatures as low as -40°F. Surfaces include treated woods, many plastics, natural and synthetic rubber, primed metal, leather, textiles, paper and fiber boards.

Pint Kit (Pint A, 1/4lb B) P/N 02-00036
 Quart Kit (Qt A, 1/2lb B) P/N 02-00037
 Gallon Kit (Gal A, 2lbs B) P/N 02-00038



FPL-16A HUGHES GLUE

This is an exceptionally fine two-part white epoxy glue for homebuilt and experimental aircraft. Not only for wood but for many other applications such as a metal to wood adhesive, metal to metal, just about anything with the exception of some plastics. It has been used by builders for many years with universal acceptance. Its low viscosity makes it very easy to work. Shelf life: Resin - more than 1 yr. Hardener - Indefinite.

Qt. Kit (1 qt. resin, 4oz hardener, Wt 4 lbs)
 P/N 02-23400



HYSOL EA-9430 GLUE

Replaces the EA-9410-2 glue. EA-9430 has the same characteristics as the EA-9410, but has a 50 minute pot life instead of the 30 minute pot life of the EA-9410 at 77°F. Used extensively in the Strojnik S2A sailplane and many other homebuilts.

P/N 02-18600



WEST SYSTEM SIX10 THICKENED EPOXY ADHESIVE

Six10 Adhesive gives you the strength and reliability of a two-part WEST SYSTEM epoxy with the convenience of a single part product. Six10 is dispensed with a standard caulking gun. Non-sagging Six10 bonds tenaciously to wood, metals, fiberglass and concrete. It cures in temperatures as low as 50°F. Working time is 42 minutes at 72°F. Cures to a solid in 5-6 hours and will take high loads in 24 hours. Cure time is faster at warm temperatures and slower in cool temperatures. Dispense mixed 2 part epoxy adhesive using a standard caulking gun. The efficient internal geometry of the 600 Mixer thoroughly blends resin and hardener in a short mixing length for good application control and a minimum of waste. Additional 600 Static-Mixers are available in packages of two or twelve.

Part No.	Description	Unit Size	Price
01-01069	Epoxy Adhesive Cartridge	190 ml	.
01-01071	Static Mixers	2 ea	.

FASTWELD 10 A/B HIGH SETTING EPOXY



Fastweld 10 A/B epoxy adhesive is a rapid-setting, two-component paste offering a convenient one-to-one mixing ratio by volume or weight. Fastweld 10 A/B epoxy adhesive produces strong bonds in a very short period. It is especially suited for bonding small parts and for repair work. Pot life: 3-4 minutes at 77° F, Cure Time: 4 hours.

Shelf life: 3 years P/N 09-03454
 3M™ EPX Pneumatic Mix Nozzle 9742..... P/N 09-01372

GORILLA GLUE TOUGHEST GLUE ON EARTH



Gorilla Glue is known as the toughest glue on planet Earth. A high strength adhesive that quickly bonds wood, metals, stones, ceramics, and more. Gorilla Glue is a versatile, interior/exterior adhesive ideal for building projects. 8 oz. bottle.

Benefits: • 100% Waterproof • Incredibly Strong and Versatile • Stainable and Paintable • Easily Sanded • More Coverage • A Long Open Working Time • Dries Light Tan • Non-toxic • Acid-Free

8oz. P/N 02-00101
 Single use (4 tubes)..... P/N 02-00225



T-88 STRUCTURAL ADHESIVE

T-88 is a non-brittle structural adhesive which gives superior finished results even when used under adverse working conditions. T-88 will cure in temperatures as low as 35°F which makes it an excellent choice for homebuilders living in colder climates. It is recommended by the builders of many types of homebuilt aircraft and is excellent for bonding aluminum, steel or wood. When fully cured, it is not affected by water, oil, gasoline and most other chemicals.

1/2 Pt Kit... P/N 02-00046 Pt. Kit..... P/N 02-00047
 Qt. Kit P/N 02-00048 Gal. Kit.... P/N 02-00049



T-88 UNIVERSAL CARTRIDGES

With the Universal Cartridge any medium to high quality caulking gun will work just fine. When you evaluate the Universal Cartridge notice that without a mixture tip it is perfect for accurately measuring small batches of adhesive. This is something that is very hard to do in a mixing cup without generating a lot of waste. Of course when the cartridge is used with the mixing tip you get both accurate measuring and thorough mixing making large, continuous gluing jobs much easier with flawless products performance. **Note:** Cartridge includes one mixing tube. Extra mixing tubes and caps are sold separately.

P/N 02-00103



REDI-MIX MIXER TUBE

The static mixer tube attaches to the cartridge with a retaining nut which screws on securely to the REDIMIX gun. The mixer tip tapers to 1/8" but may be cut back to about 1/4". Very small quantities of epoxy may be prepared in this manner without any waste or added cost..

P/N 02-90030

SCOTCH WELD 3M™ STRUCTURAL ADHESIVE



Commonly known as "Scotch Weld", this two part epoxy structural adhesive will bond wood, metal, plastics and rubber. It has a pot life of nearly 2 hours after mixing, and a 24 month shelf life. Forms flexible yet very strong bonds.

Color:Gray. 2 oz. kit P/N 02-00045

QUIK FIX EPOXY PUTTY STICKS



Quikfix BC 101 is a hand mixable, fast curing, general purpose epoxy putty stick that mixes in just one minute to provide fast repairs to many surfaces including metals, wood, glass, concrete, ceramics and numerous plastics.

One hour after mixing, QuikFix BC 101 can be drilled, sawed, sanded, filed, tapped, machined, or painted. Color: Gray (after cure).

3.5" stick P/N 01-00333
 7" stick P/N 01-00332

BOND-AIDE WOOD EPOXY PUTTY



Bond-Aide P-1500W is a wood epoxy putty compound that cures in minutes to form permanent repairs on woods, plaster, ceramics and many plastics with no shrinkage. Excellent for bonding wood to wood, wood to metal, and wood to glass or ceramics.

P-1500W has a multitude of uses in aircraft restoration, rebuilding, and repair.

1 tube 2-part Bond-Aide P-1500W P/N 02-18650/ea

G/FLEX EPOXY ADHESIVE



A toughened, versatile, liquid epoxy for permanent waterproof bonding of fiberglass, ceramics, metals, plastics, damp and difficult-to-bond woods. Modulus of elasticity of 150,000 PSI. Can absorb the stress of expansion, contraction, shock and vibration. Can be modified with West System fillers and additives, and used to wet-out fiberglass tapes and fabrics. Mixed at a 1:1 ratio, G/flex gives you 45 minutes of working time at room temperature. It reaches an initial cure in 7 to 10 hrs and full cure in 24 hrs.

Epoxy Adhesive ... P/N 01-01162

650-K Epoxy Kit - Contains 4 fl. oz. G/flex 650 resin, 4 fl. oz. G/flex 650 hardener (8 fl. oz. mixed epoxy), 2 reusable mixing stick/applicators, 2 12-cc syringes, 4 grams Adhesive Filler, 4 mixing cups, 1 pair disposable neoprene gloves, 4 alcohol cleaning pads and complete handling and repair instructions. P/N 01-01161

655-K Epoxy Repair Kit - Contains 4.5 fl. oz. G/flex 655 resin, 4.5 fl. oz. G/flex 655 hardener (9 fl. oz. of mixed epoxy), 2 reusable mixing stick/applicators, 4 alcohol cleaning pads, 1 pair disposable neoprene gloves, 10 mixing palettes and complete handling and repair instructions.

P/N 01-01163