

MACHINE SCREWS



MS35206 MACHINE SCREWS (CROSS RECESSED)

These pan head machine screws feature 60,000 psi minimum tensile strength and are cadmium plated to specification QQ-P-416, Type 2, Class 3. Manufactured from carbon steel to Federal Standard #66, these screws can be used as replacements for AN526 machine screws. Phillips head.

Part Number	Old AN515R	Dia.-Thread Size	Length (In.)	Price each
MS35206-203	-2R2	2-56	1/4	.
MS35206-204	-2R5	2-56	5/16	.
MS35206-205	-2R6	2-56	3/8	.
MS35206-206	-2R7	2-56	7/16	.
MS35206-207	-2R8	2-56	1/2	.
MS35206-208	-2R10	2-56	5/8	.
MS35206-209	-2R12	2-56	3/4	.
MS35206-212	-4R3	4-40	3/16	.
MS35206-214	-4R5	4-40	5/16	.
MS35206-215	-4R6	4-40	3/8	.
MS35206-216	-4R7	4-40	7/16	.
MS35206-217	-4R8	4-40	1/2	.
MS35206-218	-4R10	4-40	5/8	.
MS35206-219	-4R12	4-40	3/4	.
MS35206-220	-4R14	4-40	7/8	.
MS35206-221	-4R16	4-40	1	.
MS35206-222	-4R20	4-40	1-1/4	.
MS35206-223	-4R24	4-40	1-1/2	.
MS35206-226	-6R4	6-32	1/4	.
MS35206-227	-6R5	6-32	5/16	.
MS35206-228	-6R6	6-32	3/8	.
MS35206-229	-6R7	6-32	7/16	.
MS35206-230	-6R8	6-32	1/2	.
MS35206-231	-6R10	6-32	5/8	.
MS35206-232	-6R12	6-32	3/4	.
MS35206-233	-6R14	6-32	7/8	.
MS35206-234	-6R16	6-32	1	.
MS35206-235	-6R20	6-32	1-1/4	.
MS35206-236	-6R24	6-32	1-1/2	.
MS35206-238	-6R32	6-32	2	.
MS35206-241	-8R4	8-32	1/4	.

Part Number	Old AN515R	Dia.-Thread Size	Length (In.)	Price each
MS35206-242	-8R5	8-32	5/16	.
MS35206-243	-8R6	8-32	3/8	.
MS35206-244	-8R7	8-32	7/16	.
MS35206-245	-8R8	8-32	1/2	.
MS35206-246	-8R10	8-32	5/8	.
MS35206-247	-8R12	8-32	3/4	.
MS35206-248	-8R14	8-32	7/8	.
MS35206-249	-8R16	8-32	1	.
MS35206-250	-8R20	8-32	1-1/4	.
MS35206-251	-8R24	8-32	1-1/2	.
MS35206-252	-8R28	8-32	1-3/4	.
MS35206-253	-8R32	8-32	2	.
MS35206-261	-10R6	10-24	3/8	.
MS35206-262	-10R7	10-24	7/16	.
MS35206-263	-10R8	10-24	1/2	.
MS35206-264	-10R10	10-24	5/8	.
MS35206-265	-10R12	10-24	3/4	.
MS35206-267	-10R16	10-24	1	.



MS35207 MACHINE SCREWS (CROSS RECESSED)

These pan head machine screws have 55,000 psi minimum tensile strength and are cadmium plated to Specification QQ-P-416, Type 2, Class 3. Manufactured from carbon steel per Federal Standard #66.

Part Number	Old AN520R	Diameter Thread Size	Length (In.)	Price each
MS35207-260	-10R5	10-32	5/16	.
MS35207-261	-10R6	10-32	3/8	.
MS35207-262	-10R7	10-32	7/16	.
MS35207-263	-10R8	10-32	1/2	.
MS35207-264	-10R10	10-32	5/8	.
MS35207-265	-10R12	10-32	3/4	.
MS35207-266	-10R14	10-32	7/8	.
MS35207-267	-10R16	10-32	1	.
MS35207-268	-10R20	10-32	1-1/4	.
MS35207-269	-10R24	10-32	1-1/2	.
MS35207-270	-10R28	10-32	1-3/4	.
MS35207-271	-10R32	10-32	2	.