

MACHINE SCREWS

AN525 WASHER HEAD SCREWS



High-strength machine screws fabricated from alloy steel per specification AMS6300. Tensile strength 125,000 PSI. Cadmium plated per QQ-P-416, Type II, Class 3. Cross-recessed head.

Dash No.	Length	Grip in.	Thread Size	Price
AN525-832R4	1/4	1/32	8-32	.
AN525-832R5	5/16	--	8-32	.
AN525-832R6	3/8	1/32	8-32	.
AN525-832R7	7/16	1/16	8-32	.
AN525-832R8	1/2	1/8	8-32	.
AN525-832R9	9/16	5/32	8-32	.
AN525-832R10	5/8	7/32	8-32	.
AN525-832R11	11/16	9/32	8-32	.
AN525-832R12	3/4	11/32	8-32	.
AN525-832R14	7/8	15/32	8-32	.
AN525-832R16	1	19/32	8-32	.
AN525-832R18	1-1/8	23/32	8-32	.
AN525-832R20	1-1/4	27/32	8-32	.
AN525-832R22	1-3/8	31/32	8-32	.
AN525-832R24	1-1/2	1-3/32	8-32	.
AN525-8R9	9/16	5/32	8/36	.
AN525-10R4	1/4	--	10-32	.
AN525-10R5	5/16	--	10-32	.
AN525-10R6	3/8	1/32	10-32	.
AN525-10R7	7/16	1/16	10-32	.
AN525-10R8	1/2	1/8	10-32	.
AN525-10R9	9/16	5/32	10-32	.
AN525-10-9 (Slotted)	9/16	5/32	10-32	.
AN525-10R10	5/8	7/32	10-32	.
AN525-10R11	11/16	9/32	10-32	.
AN525-10R12	3/4	11/32	10-32	.
AN525-10R14	7/8	15/32	10-32	.
AN525-10R16	1	19/32	10-32	.
AN525-10R18	1-1/8	23/32	10-32	.
AN525-10R20	1-1/4	27/32	10-32	.
AN525-10R22	1-3/8	31/32	10-32	.
AN525-10R24	1-1/2	1-3/32	10-32	.
AN525-416R6	3/8	1/32	1/4-28	.
AN525-416R7	7/16	1/16	1/4-28	.
AN525-416R8	1/2	1/8	1/4-28	.
AN525-416R9	9/16	5/32	1/4-28	.
AN525-416R10	5/8	7/32	1/4-28	.
AN525-416R12	3/4	11/32	1/4-28	.
AN525-416R14	7/8	15/32	1/4-28	.
AN525-416R16	1	19/32	1/4-28	.
AN525-416R18	1-1/8	23/32	1/4-28	.
AN525-416R20	1-1/4	27/32	1/4-28	.

AN526C STAINLESS STEEL MACHINE SCREWS



Stainless steel Phillips and slotted, Use slotted screws for antiques.

Thread	Length	Phillips Part No.	Price Ea.
4-40	1/2	AN526C-440R8	.
6-32	1/4	AN526C-632R4	.
	3/8	AN526C-632R6	.
	1/2	AN526C-632R8	.
	5/8	AN526C-632R10	.
	3/4	AN526C-632R12	.
	1	AN526C-632R16	.
8-32	1/4	AN526C-832R4	.
	3/8	AN526C-832R6	.
	1/2	AN526C-832R8	.
	5/8	AN526C-832R10	.
	3/4	AN526C-832R12	.
	1	AN526C-832R16	.
10-32	1/4	AN526C-1032R4	.
	3/8	AN526C-1032R6	.
	1/2	AN526C-1032R8	.
	5/8	AN526C-1032R10	.
	3/4	AN526C-1032R12	.
	1	AN526C-1032R16	.
	1-1/4	AN526C-1032R20	-----
	1-1/2	AN526C-1032R24	.
1/4-20	1/2	AN526C-420R8	.
1/4-28	1/2	AN526C-428R8	.
	3/4	AN526C-428R12	.
	1-1/8	-----	---

Thread	Length	Slotted Part No.	Price Ea.
4-40	1/2	-----	---
6-32	1/4	AN526C-632-4	.
	3/8	-----	---
	1/2	AN526C-632-8	.
	5/8	AN526C-632-10	.
	3/4	-----	---
	1	AN526C-632-16	.
8-32	1/4	-----	---
	3/8	-----	---
	1/2	AN526C-832-8	.
	5/8	AN526C-832-10	.
	3/4	-----	---
	1	AN526C-832-16	.
10-32	1/4	-----	---
	3/8	AN526C-1032-6	.
	1/2	AN526C-1032-8	.
	5/8	AN526C-1032-10	.
	3/4	AN526C-1032-12	---
	1	-----	---
	1-1/4	-----	---
	1-1/2	-----	---
1/4-20	1/2	-----	---
1/4-28	1/2	-----	---
	3/4	-----	---
	1-1/8	AN526C-428-18	.

Note: Some sizes of AN526C screws are furnished as commercial equipment as AN screws are no longer available.