

SCREWS

NAS333 AND NAS334 SCREWS



- Material - Alloy Steel (8740) • Heat Treat - 160,000 - 180,000 PSI
- Finish - Cadmium Per QQ-P-416 Type II

Thread	Grip	Length	Part No.	Price
10-32	0.125	0.531	NAS333CPA4	.
10-32	0.188	0.594	NAS333CPA4-5	.
10-32	0.250	0.656	NAS333CPA5	.
10-32	0.312	0.719	NAS333CPA5-5	.
10-32	0.375	0.781	NAS333CPA6	.
10-32	0.500	0.906	NAS333CPA7	.
10-32	0.625	1.031	NAS333CPA10	.
1/4-28	0.188	0.657	NAS334CPA5	.
1/4-28	0.312	0.781	NAS334CPA6	.
1/4-28	0.438	0.907	NAS334CPA7	.
1/4-28	0.562	1.031	NAS334CPA10	.

NAS1580 SCREWS



- Offset Cruciform 100 Deg Flush Head • Material - Alloy Steel (8740) or Cres. (A-286) • Heat Treat - 160,000 - 180,000 or PSI 160,000 - 190,000 PSI • Finish - Cadmium Per AmsQQ-P-416 TYPE II or Passivate Per Ams 2700 • Thread: 10-32

Dash No.	Heat Treat	Finish	Grip	Length	Part No.	Price
Alloy Steel (8740)						
A3T2	160,000 - 180,000 PSI	Cadmium Per Ams QQ-P-416 TYPE II	0.125	0.487	NAS1580A3T2	.
A3T3			0.187	0.549	NAS1580A3T3	.
A3T4			0.250	0.613	NAS1580A3T4	.
A3T5			0.312	0.675	NAS1580A3T5	.
Cres. (A-286)						
C3T3	160,000 - 190,000 PSI	Passivate Per Ams 2700	0.187	0.549	NAS1580C3T3	.
C3T4			0.250	0.613	NAS1580C3T4	.

NAS1581 SCREWS



- Offset Cruciform 100 Deg Flush Head • Material - Alloy Steel (8740) or Cres. (A-286) • Heat Treat - 160,000 - 180,000 PSI or 160,000 - 190,000 PSI • Finish - Cadmium Per AmsQQ-P-416 TYPE II or Passivate Per Ams2700 • Thread: 10-32

Dash No.	Heat Treat	Finish	Grip	Length	Part No.	Price
Alloy Steel (8740)						
F3T2 Plain Cruciform	160,000 - 180,000 PSI	Cadmium Per Ams QQ-P-416 TYPE II	0.125	0.487	NAS1581F3T2	.
F3T3 Plain Cruciform			0.187	0.549	NAS1581F3T3	.
F3T4 Plain Cruciform			0.250	0.613	NAS1581F3T4	.
F3T5 Plain Cruciform			0.312	0.675	NAS1581F3T5	.
F3T8 Plain Cruciform			0.500	0.863	NAS1581F3T8	.
F3R2 Ribbed Cruciform			0.125	0.487	NAS1581F3R2	.
F3R3 Ribbed Cruciform			0.187	0.549	NAS1581F3R3	.
F3R4 Ribbed Cruciform			0.250	0.613	NAS1581F3R4	.
Cres. (A-286)						
C3T2	160,000 - 190,000 PSI	Passivate Per Ams 2700	0.125	0.487	NAS1581C3T2	.
C3T3			0.187	0.549	NAS1581C3T3	.
C3T4			0.250	0.613	NAS1581C3T4	.

NAS1802 PHILLIPS HEX HEAD SCREWS



- Screw, Phillips Hex Head • Material - A-286 Corrosion Resisting Steel
- Finish - Passivate Per QQ-P-35

NAS1802 Dash No.	Thread Size	Length	Part No.	Price
06-5	6-32	0.312	NAS1802-06-5	.
06-6	6-32	0.375	NAS1802-06-6	.
06-7	6-32	0.438	NAS1802-06-7	.
06-8	6-32	0.500	NAS1802-06-8	.
06-9	6-32	0.562	NAS1802-06-9	.
08-5	8-32	0.312	NAS1802-08-5	.
08-6	8-32	0.375	NAS1802-08-6	.
08-7	8-32	0.438	NAS1802-08-7	.
08-8	8-32	0.500	NAS1802-08-8	.
08-9	8-32	0.562	NAS1802-08-9	.
08-10	8-32	0.625	NAS1802-08-10	.
08-11	8-32	0.688	NAS1802-08-11	.
08-12	8-32	0.750	NAS1802-08-12	.
08-16	8-32	1.000	NAS1802-08-16	.
3-5	10-32	0.312	NAS1802-3-5	.
3-6	10-32	0.375	NAS1802-3-6	.
3-7	10-32	0.438	NAS1802-3-7	.
3-8	10-32	0.500	NAS1802-3-8	.
3-9	10-32	0.562	NAS1802-3-9	.
3-10	10-32	0.625	NAS1802-3-10	.
3-11	10-32	0.688	NAS1802-3-11	.
3-12	10-32	0.750	NAS1802-3-12	.
3-13	10-32	0.812	NAS1802-3-13	.
3-14	10-32	0.875	NAS1802-3-14	.
3-15	10-32	--	NAS1802-3-15	.
3-16	10-32	1.00	NAS1802-3-16	.

NAS4403 SCREWS



- Tri-Slot 100 Deg Flat Head, Close Tolerance • Material - Alloy Steel (8740) • Heat Treat - 160,000 - 180,000 • Finish - Cadmium Per AmsQQ-P-416 TYPE II • Thread: 10-32

NAS4403 Dash No.	Grip	Length	Part No.	Price
-2	0.125	0.448	NAS4403-2	.
-3	0.187	0.511	NAS4403-3	.
-4	0.250	0.573	NAS4403-4	.
-5	0.312	0.635	NAS4403-5	.
-6	0.374	0.698	NAS4403-6	.

NAS7403 SCREWS



- Phillips 100 Deg Flush Head, Close Tolerance, Short Thread • Material - Alloy Steel (8740) • Heat Treat - 160,000 - 180,000 • Finish - Cadmium Per AmsQQ-P-416 TYPE II • Thread: 10-32

NAS7403 Dash No.	Grip	Length	Part No.	Price
-2	0.125	0.448	NAS7403-2	.
-3	0.187	0.511	NAS7403-3	.
-4	0.250	0.573	NAS7403-4	.
-5	0.312	0.635	NAS7403-5	.
-6	0.374	0.698	NAS7403-6	.
-7	0.438	0.761	NAS7403-7	.