

DAVTRON INSTRUMENTS

MILITARY CHRONOMETER



- Military clock • Two button control system
- Control switch has remote capability • Sunlight readable displays • N.V.G. Filter, Green A or BG7B
- Manual dimming of the display • Full 6 digit display selectable, GMT, LT, ET • Elapsed time is count up or down • Keep alive battery (2 year life) • GMT full 6 digit hours/minutes/seconds • Local Time, 24 hour, 4 digit

Description	Part No.	Price
GMT, LT & ET Clock with night vision compatibility for military (BG7B)	11-08021	.
GMT, LT & ET Clock with night vision compatibility for military (Green A)	11-08022	.

DENSITY & PRESSURE ALTITUDE MODEL 655



Front Mount



Rear Mount



Front Mount



Rear Mount

- OAT (F) & OAT (C) • Pressure & Density Altitude With Pressure ALT. Alarm • Aircraft Voltage with Flashing Alarm • Bright Sunlight Readable Displays
- Input Voltage 11 TO 28 Volts • Complete with 12 FT. Digital Probe

Description	Part No.	Price
Front Mount	10-24515-1	.
Rear Mount	10-24515-2	.

DIGITAL VOLTMETER OUTSIDE AIR TEMPERATURE MODEL 303

- OAT (F) & OAT (C) • Aircraft Voltage with Flashing Alarm • Bright Sunlight Readable Displays
- Input Voltage 11 TO 28 Volts • Complete with 12 FT. Digital Probe.

Description	Part No.	Price
Front Mount	10-24565-14-1	.
Rear Mount	10-24565-14-2	.

DIGITAL VOLTMETER AMMETER MODEL 475VA/475VAA



M475VA



M475VAA

- Low current drain .001 amp
- Plus 100.0 volt D.C. range
- 1.3" case depth
- Sunlight readable
- One tenth volt resolution
- Plus or minus 100.0 amp range
- 2 1/4 Standard mount
- 5, 14, or 28 volt back lighting
- One tenth amp resolution

The M475VAA has dual shunts and can read voltage and two current flows (M475VA has a single shunt). The 475VA and the 475VAA were designed for low current drain and are also used in standby and emergency battery packs. One example of safety is if the alternator fails, you can monitor the load current out of the battery.

Description	Part No.	Price
Volt/Amm Meter 14V Lighting (Single Shunt)	10-03319	.
Volt/Amm Meter 28V Lighting (Single Shunt)	10-03320	.
Volt/Amm Meter 14V Lighting (Double Shunt)	10-03321	.
Volt/Amm Meter 28V Lighting (Double Shunt)	10-03322	.
Volt/Amm Meter 14V Lighting (Single Shunt) With Night Vision Compatibility Green A	10-04562	.
Volt/Amm Meter 28V Lighting (Single Shunt) With Night Vision Compatibility Green A	10-04564	.
Volt/Amm Meter 14V Lighting (Double Shunt) With Night Vision Compatibility Green A	10-04566	.
Volt/Amm Meter 28V Lighting (Double Shunt) With Night Vision Compatibility Green A	10-04567	.

DAVTRON PROBES

Description	Part No.	Price
Probe-12ft-wht-c307ps Temperature Probe 12ft Coax (Analog) 301.303.307.655 & 803	11-04603	.
Probe-12ft-wht-c307psm Temperature Probe 12ft Coax (Analog Ad590mh, Enhance Precision Temperature) 301.303.307.655 & 803	11-20896	.
Probe-12ft-wht-d Temp Probe 12ft White Digital (For Units With "D" In The Serial #: Models 301, 303, 307 & 655)	11-10717	.
Probe-nut Nut For Temp. Probe	11-09416	.
Probe-7ft-rb Temp Probe 7ft Red/blk Twisted (Analog) 301.303.307 & 655 Note: Units With "D" In The Serial # Use A Digital Probe	10-00653	.
Probe-2ft-rb-mini Temp. Probe (Analog). 307cd & 307fd	10-07464	.
C307prf11-a Temperature Probe 11ft White (Analog)	10-07707	.
Davtron 9 Pin Female Connector Assembly	10-07466	.

DIGITAL OUTSIDE AIR TEMPERATURE

MODEL 301



- OAT (F)
- OAT (C)
- Bright Sunlight Readable Displays
- Input Voltage 11 TO 28 Volts.
- Complete with 12 FT. Digital Probe.

Description	Color	Part No.	Price
O.A.T. Celsius (301 C),	Amber LED	10-08312	.
301C 3 Pin Connector for Probe	Amber LED	10-03316	.
O.A.T. Fahrenheit (301 F)	Amber LED	10-08512	.
301F 3 Pin Connector for Probe	Amber LED	10-03317	.
O.A.T. Celsius,	Green LED	10-04543	.
O.A.T. Celsius,	White LED	10-04544	.
301C 3 Pin Connector For Probe	Green LED	10-04545	.
301C 3 Pin Connector For Probe	White LED	10-04546	.
O.A.T. Fahrenheit	Green LED	10-04547	.
O.A.T. Fahrenheit	White LED	10-04548	.
301F 3 Pin Connector For Probe	Green LED	10-04549	.
301F 3 Pin Connector For Probe	White LED	10-04551	.



M307FC



M307FCI



M307FCE

- OAT (F) & OAT (C) Voltage
- Input Voltage 11 TO 28 Volts.
- Bright Sunlight Readable Displays
- Complete with 12 FT. Digital Probe.

Description	Part No.	Price
O.A.T. F & C (307FC)	10-08513	.
O.A.T. F & C Cabin Air (307FCI)	11-05881	.
O.A.T. F & C & Voltmeter (307FCE)	10-04552	.



Description	Part No.	Price
Celsius Differential Intercooler (307 CD)	10-03318	.
Fahrenheit Differential Intercooler (307 FD)	11-05882	.



MODEL 450



MODEL 451

- Aircraft Voltage with Flashing Alarm • Aircraft Voltage (451)
- Bright Sunlight Readable Display • Bright Sunlight Readable Display
- Input Voltage 11 TO 28 Volts. • Minimum panel Space
- Input Voltage 11 TO 28 Volts.

Description	Part No.	Price
Voltmeter (450), Amber LED	10-24505	.
Voltmeter (450), Amber LED, Remote Sensing	10-04555	.
Voltmeter (450), Green LED	10-04553	.
Voltmeter (450), Green LED, Remote Sensing	10-04556	.
Voltmeter (450), White LED	10-04554	.
Voltmeter (450), White LED, Remote Sensing	10-04557	.
Voltmeter (451), Red LED, Remote Sensing	10-04558	.

ACCESSORIES / REPLACEMENT PARTS

Description	Part No.	Price
KW-105G Display for Model 303, 307, 655, 880, & 903	11-04611	.
KW-115G Display for Model 303, 655, 850, 877, & 880	11-04612	.
KW-505F Digital Display for model 811B	11-04613	.
800 Series Alarm Son-Alert	11-04610	.
Temp Probe - 7Ft Red/Black Twisted (Analog)	10-00653	.
Temp Probe - 12Ft COAX C307PS (Analog)	11-04603	.
Temp Probe 12Ft COAX D307PS (Digital)	11-10717	.

See our website for additional sizes.