

HANDHELD BATTERIES – BECKER AVIONICS

BATTERIES AND BATTERY CHARGERS FOR HANDHELDS

Battery Model	Description	Part No.	Price
For Icom A24/A6			
BP-210N	7.2V 2000mAh Ultra long life	11-08251	.
BP-211N	Lightweight, Ultra long life. Li-On charger required.	11-08254	.
EMS-211	Rapid Desktop Cgr for BP-211/N	11-08256	.
For ICOM A23/A5 Handheld aviation radios-			
BP-197H	Alkaline Battery pack	11-01082	.
BP-200XL	9.6v 1450 mAh long Life Ni-MH	11-06351	.
BP-200L	9.6V 850mAh	11-08274	.
CP-12L	12VDC Cig Lighter for A5	11-08249	.
For ICOM A-4 Handheld aviation radios-			
BP-196	9.6v 1500 mAh pk	11-00227	.
EMS-196	Desktop Fast Charger BP-195/196	11-08248	.
For ICOM A-22 & A-3 radios-			
CM-166	NiMH Battery 12.0v 1200 mAh	11-00228	.
EMS-166	Desktop Charger for CM-166	11-08236	.
EC-166	Wall charger for CM-166	11-08234	.
BC-79A	Desktop Charger	11-18557	.
WC-166	Battery Charger	11-08234	.
For ICOM IC-A14 / IC-A14S Handheld aviation radios-			
BP-232N	Operating Time: 15.5 hours	11-08231	.
For ICOM A-20, A-21, & Delcom-			
CM-7x	13.2v 1000 mAh pk	11-00230	.
IC-WC	Wall charger for CM-7 / CM-7X	11-08237	.
IC-8	8 cell AA case 3-1/4" tall	11-08246	.
IC-CP	Car Power/Charge cord	11-00351	.
For ICOM R-1 radios-			
BP-83	7.2v 600 mAh pk	11-00233	.
BP-83xh	7.2v 1500 mAh pk	11-00234	.
BC-79A	Desktop Quick Charger	11-18557	.
Icom Chargers			
CP-11L	DC Power/Charge Cord for ICOM IC-T90A, IC-91AD, IC-A24, IC-A5	11-06348	.
EMS-201	7.2V thru 13.2V Ni-cd & Ni-MH	11-08245	.
EMS-210N	Smart charger for ICOM	11-06350	.
EMS-232	Rapid Desktop Charger for Icom-style Lithium ION Btlys	11-08233	.
EMS-30i	Desktop smart-quick charger.	11-06352	.
For Yaesu Aviator Pilot & Aviator Pro nav/com radios-			
FNB-41xh	9.6v 1000 mAh pk	11-00237	.
FNB-47xh	7.2v 1800 mAh pk	11-00238	.
FNB-41xs	9.6v 1450 mAh pk	11-06354	.
EMS-41/47	Rapid Cgr for FNB-40/41/47	11-08244	.
FNB-80LI	7.2V 1600mAh Yaesu & Vertex	11-08268	.
CBE-41	Battery Eliminator	11-06355	.
CBE-80	Battery Eliminator Cig Lighter	11-08269	.
E-DC-SBA	DC Power Cord, Cig Lighter	11-08241	.
EM-57-83	Super Desktop Charger	11-08239	.
For Bendix/King radios-			
BP-KX99	10.0v 1500 mAh pk	11-00240	.
KX-99XH	10.0V 2700 mAh	11-08257	.
IC-CP	Car Power/Charge cord	11-00351	.
KX-99	Battery case, 8-cell AA (BP-99A)	11-08258	.
For STS handheld radios-			
BP-ST5+	7.2v 1400 mAh pk	11-00241	.
WC-ST5	Wall Charger	11-00352	.
For Bearcat/Uniden 100/200/250XLT-			
For Bearcat/Uniden 2500XLT, 3000XLT, & 3500XLT-			
BP-2500x	6.0v 1000 mAh pk	11-00322	.
For Bearcat/Uniden Trunk Tracker & Sportcat-			
BC-120	4.8v 1000 mAh pk	11-00323	.
BC-120x	4.8v 1500 mAh pk	11-00324	.
BP-120XE	4.8V 2000 mAh Long Life	11-08272	.
BP-120XX	4.8V 2500 mAh	11-08273	.
BP-120 80	4.8v 800 mAh pk	11-08270	.
BP-120 110	4.8v 1100 mAh pk	11-08271	.
For Santec/Narco radios-			
BP-800	9.6v 600 mAh pk	11-00242	.
BP-800sh	9.6v 1000 mAh pk	11-00325	.
Standard C228A/C528A/C628A, etc.			
CNB-152XS	12V 1800mAhr NiMH	11-08261	.
CNB-152XH	12V 1200mAh Long Life	11-08259	.
CSA-181	Quick Desktop Charger	11-08266	.
For Bose Aviation Headset Series 1			
BP-A	14.4v 1250 mAh	11-00243	.
Battery Eliminators			
CBE-152	DC Battery Eliminator for standard-ADI-JRC radios	11-08262	.
CBE-196	Battery Eliminator for ICOM	11-08247	.
CBE-83	12VDC, 5W, Voltage & Current limiting, & noise filter!	11-08238	.

BECKER AR 6201 TRANSCEIVER



AR6201 series of square sized VHF transceivers from Becker are a family of affordable airborne radios optimized by their functionalities, state of the art technology, compact dimensions, and low weight for many different aircraft categories in general aviation, from smaller to larger aircraft. The radios fit in any 2 1/4 inch cut out for easy installation and the different models are equipped with sunlight readable LC displays and high performance transmitters with 6 or 10 watts power output, continuous power supply from 10.25 to 33 V DC, 8.33 kHz / 25 kHz channel spacing, sensitive receiver, VOX intercom and many other features. • 8.33 or 25 kHz • Supply voltage 9-33 V DC • 6 W or 10 W transmit power • VOX / INTERCOM • Scan (SCN) mode active/preset frequency • Tandem Operation. **Model No.** AR6201-(022) • **Channel Spacing:** VHF transceiver 6W, 8.33/25kHz spacing, blue white backlight LC - display Article - No. 0636.399 - 910P/N 11-08550 AR6201 COM Harness 3.7mP/N 11-18178

BECKER GK 615 PORTABLE VHF STATION



The carrying case contains the battery, speaker, antenna socket, the 5 way DIN socket for the micro- phone or microphone speaker and the voltage converter. A microphone, a headset or a helmet (ultra- light) can be connected to the 5-way DIN socket. The built-in battery is a maintenance-free recharge- able 12 V / 2 Ah dry lead acid battery. The transmitter power is approximately 5 to 7 W. Charging voltage can be varied between 10 V and 32 V. Charging time approx. 8 hours. The nominal operating time for the portable VHF station is approximately 6 hours at a keying ratio of 1:10 normal ra- dio traffic) and transmitter output power of 5 W. Features: • Frequency Range: 118.000 MHz to 136.990 MHz • Channel Spacing: 8.33 or 25 kHz • Channel Selection: 8.33 or 25 kHz (selectable) • RF-Output Power: > 6 W (carrier power) • Receiver Sensitivity: > 12 dB sinad for 2 uV.

Model No.	Watts	Description	Part No.	Price
0940.472 923	5	GK 615-5 Portable VHF Station	11-12319	.
0940.432 923	10	GK 615-10 Portable VHF Station	11-12320	.



BECKER AR6203 VHF / AM TRANSCEIVER

The AR6203 VHF-AM transceiver is smaller and lighter than its forerunner due to implementation of state-of-art DSP (Digital Signal Processing) technology it is designed in a 160mm format and is equipped with a highly efficient AM transmitter, a very sensitive receiver and a full graphic LC-display that allows easy reading under all light conditions, including full sun light readability. Push button and display illumination can be dimmed.

Description	Part No.	Price
AR6203-012: 8.33/25kHz Switchable, 10W	11-14415	.

BECKER GT6203 VHF / AM GROUND TRANSCEIVER



Designed for operations at airfields and airports in a very demanding environment, the GT6203 offers latest technology and comfortable operation on all frequency channels in the aeronautical frequency range, adjustable in 25 kHz steps as well as in 8.33 kHz steps. The user friendly operator menu and the extensive setup possibilities allow a very personal setup for the user. The large, clear and dazzle-free LC display shows the active frequency and either the standby frequency or memory channel. With an output power of 6W or 10W, the transmitter is strong enough for medium range communications, ensuring a low cost of ownership for the customer. Derived from its airborne counterpart AR6203, the GT6203 is the robust, reliable and flexible solution for your ground operations. 6 WattP/N 11-19086 10 WattP/N 11-19087