

PERSONAL LOCATOR BEACONS

ARTEX ELT 4000 GPS / 406 / 121.5



The ARTEX ELT 4000 is a transport-grade Emergency Locator Transmitter (ELT) that utilizes alkaline batteries. This innovative power source means that the ELT 4000 is completely exempt from FAA special condition requirements. ARTEX ELT 4000 cost of ownership benefits include a lower battery expense per cycle, no hazmat shipping and easy disposal. An integrated NAV interface (ARINC429) omits the requirement and expense of installing a separate NAV interface unit. The ARTEX ELT 4000 provides a

quick-and-easy retrofit opportunity with flexible installation options such as a two-wire remote switch that does not require any aircraft power. ELT 4000 is TSO approved with Legacy Switch and Antenna Systems to facilitate retrofit. The mounting tray assembly matches the legacy ARTEX C and B Series ELT installation and thereby further reduces engineering costs.

Base PackP/N 11-16253
With Alkaline Battery Only.....P/N 11-16255
With Blade Antenna/Remote.....P/N 11-16257

ARTEX C406 ELT

Operates on the latest SAR frequency of 406.025 MHz & 121.5 243 MHz. Ready to connect to the Artex ELT NAV interface. Includes ELT transmitter, LiMnO2 5-year battery pack, mounting bracket, remote switch, horn/buzzer, coax cables, high speed blade antenna, installation hardware, and installation and operation manual. The C406-1 is approved for aircraft operating speeds up to Mach 1, and C406-2 is approved for speeds up to 350 knots. COSPAS/SARSAT, FAA TSO C126 & JTSO-2C126 Approved.



C406-1 ELT with 110-340 Blade Ant. U.S ..P/N 11-02984
C406-1 ELT with 110-340 Blade Ant. Intl.....P/N 11-09320
CC2 ELT with Rod Antenna.....P/N 11-02985

ARTEX 2-WIRE REMOTE INTERFACE SYSTEM



This product allows an upgrade to an Artex 5-Wire 406 MHz ELT using an existing 2-wire configuration. The 2-Wire Remote Interface allows two wires from the existing wiring harness to connect the cockpit remote switch to the ELT for simplified, cost-efficient installation.

P/N 11-07776

ARTEX ACCESSORIES

ARTEX WIRE WHIP ANTENNA



Black whip antenna with inductor. For use with 121.5 and 243 MHz. Designed for speeds up to 200 knots TAS

Specifications: • Frequency: 121.5, 243 MHz & • VSWR: 2.0:1 Max for 121.5/243 MHz • Polarization: Vertical • Height: 17.4" Max • Connector: RF Connector, BNC Series (female) • Temperature: -55° C to + 85° C • Altitude: 50,000 feet • Air Speed: 200 Knots TAS • Color: Black

P/N 110-324

ORDER ONLINE!

www.aircraftspruce.com

- 100,000 Parts!
- 24 Hour Access!
- Fast, Easy Navigation!

ACR RESQLINK™ VIEW BUOYANT PLB WITH DIGITAL DISPLAY



Small but resilient, the ResQLink View has been professionally engineered and tested to ensure it can withstand even the harshest elements. This buoyant Personal Locator Beacon requires no subscription for use and includes a digital display providing live status and GPS coordinates. Whether on land, at sea, or in the air, trust that the ResQLink's satellite precision and military durability, puts rescue in the palm of your hands.

Features: • No Subscription Required • GPS and Galileo GNSS • Built-In Buoyancy • Strobe and Infrared Strobe • Global Coverage • MEOSAR Compatible • Small and lightweight • 5 year battery life • 28 hours Operational Life** • Multi-function Clip System Included • Exclusive ACR Skins included with purchase (customize your beacon and tailor it to your lifestyle and preferred activities) • **Based on test report from accredited laboratory.

P/N 11-17216

ACR RESQLINK™ 400 BUOYANT PLBS



Small but resilient, the ResQLink 400 has been professionally engineered and tested to ensure it can withstand even the harshest elements. This buoyant Personal Locator Beacon requires no subscription for use and can be utilized to enhance your safety in a wide variety of environments. Whether on land, at sea, or in the air, trust that the ResQLink's satellite precision and military durability, puts rescue in the palm of your hands.

Features: • No Subscription Required • GPS and Galileo GNSS • Built-In Buoyancy • Strobe and Infrared Strobe • Global Coverage • MEOSAR Compatible • Small and lightweight • 5 year battery life • 24+ hours Operational Life** • Multi-function Clip System Included • **Based on test report from accredited laboratory

USAP/N 11-17215
International.....P/N 11-17489

ACR RESQLINK™ VIEW RLS



Small but resilient, the ResQLink View RLS has been professionally engineered and tested to ensure it can withstand even the harshest elements. This buoyant Personal Locator Beacon requires no subscription for use, boasts a digital display providing live status and GPS coordinates, and includes the new Return Link Service (RLS) feature. Beacons with RLS provide confirmation to the user that their beacon's emergency distress message has been received and that their location has been detected. RLS works by sending a signal back through the Cospas Sarsat satellite network to confirm to the beacon user that the distress message from a beacon has been received and their location has been detected. User confirmation is distinctly indicated by a flashing blue light and a corresponding confirmation message on the digital display.

P/N 11-19372



ARTEX BNC CABLE - 15 ft female BNC to BNC coax cable for use with 406 ELT series.

P/N 11-08130