

CHERRY RIVET TOOLS



CHERRYLOCK POWER RIVETER KIT G784CLRA

Installs: 1/8" to 3/16", NAS 1398/9. Type & Cherry Lock. **Includes:** G784 Cherry Universal Power Riveter 12" High, 8 lbs., 15/16" Stroke. H681-4C CherryLock H681 Pulling Heads Dia. 1/8" Dim. A=208 B=341. H681-5C CherryLock Pulling Head 5/32" D. H681-6C CherryLock H681 Pulling Heads Dia. 3/16" Dim. A=335 B=386. P1395 Molded Carrying Case. TLC852 CherryLock Selector Card. TLC864 CherryLock Process Manual. 269C3 CherryMAX Grip Gauge. 700A77 Bleeder Bottle.

P/N 12-02999



CHERRY RIVETER SERVICE KIT G747KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G747.

P/N 12-02996



CHERRY RIVETER SERVICE KIT G746KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G746A.

P/N 12-02994



CHERRY RIVETER SERVICE KIT G704KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G704B.

P/N 12-02990



CHERRY RIVETER SERVICE KIT G689KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G689.

P/N 12-02984



BLIND BOLT RIVETER TOOL KIT G84-MBK

Installs: 5/32", 3/16" & 1/4" MS Blind Bolt

Includes: • G84 Power Riveter Cherry- Stroke: 9/16", Pulling Force: 5, 750 lbs (2,608 kgs), Weight: 7.7 lbs (3.5 kgs) • H83B-5MB Pulling Head MaxiBolt 5/32" D • H83B-6MB Pulling Head MaxiBolt 3/16" D G83/G84 • H84A-8MB Pulling Head MaxiBolt 1/4" D G84

• P1395 Molded Carrying Case • TLC872 Cherry MaxiBolt Card • 269B12 MaxiBolt Gauge • 670A20 Stem Catcher Bag • 700A77 Bleeder Bottle.

P/N 12-03015

CHERRYMAX POWER RIVETER KIT G747CMR



Installs: NAS 9301 to 9312 (1/8" to 3/16"). MS90353/4. MS21140/1. TAF "S" TYPE (1/8" & 5/32"). MS20604/5 (3/32"). **Includes:** G747 Cherry Lightweight - Installs CherryMAX Rivets. H701B-456 Pulling Head Straight 3/4" x 1-3/4". H747-3NPR Pulling Head. H753A-456 CherryMAX Pulling Heads RT Angle 2-1/4"x5-7/16"x3/8". H781-456 Cherry Pulling Head Offset 1/8"-5/32"-3/16". P1393 Plastic Box. 269C3 CherryMAX

Grip Gauge. 670A20 Stem Catcher Bag. 700A77 Bleeder Bottle. All Necessary Manuals. P/N 12-02997



CHERRY POWER RIVETER KIT G746ACMRB

Installs: -4, -5, -6 CherryMAX. **Includes:** G746A Power Riveter Cherry 1/8", 5/32", 3/16" "A" Rivets. H701B-456 Pulling Head Straight 3/4" x 1-3/4". H753A-456 CherryMAX Pulling Heads RT Angle 2-1/4"x5-7/16"x3/8". H781-456 Cherry Pulling Head Offset 1/8"-5/32"-3/16". P1393 Plastic Box. 269C3 CherryMAX

Grip Gauge. 670A20 Stem Catcher Bag. 700A77 Bleeder Bottle. All Necessary Manuals. P/N 12-02992



CHERRYLOCK POWER RIVETER KIT G746ACMRW

Installs: SST & -3, -4, -5, -6. CherryLock 'A'. **Includes:** G746A Power Riveter Cherry 1/8", 5/32", 3/16" "A" Rivets. H955-3 Pulling Head. H955-4 Pulling Head H955-5 Pulling Head. H955-6 Pulling Head. P1393 Plastic Box. 269C3 CherryMAX Grip Gauge. 670A20 Stem Catcher Bag. 700A77 Bleeder Bottle. All Necessary Manuals. P/N 12-02993



CHERRY POWER RIVETER KIT G704BCMR

Installs: -4, -5, -6 CherryMax. **Includes:** 6704B Power Riveter - Cap = 1/8-3/16" Wt. = 4 1/2 lbs. H701B-456 Pulling Head Straight 3/4" x 1-3/4". H753A-456 CherryMAX Pulling Heads RT Angle 2-1/4"x5-7/16"x3/8". H781-456 Cherry Pulling Head Offset 1/8"-5/32"-3/16". P1393 Plastic Box. TLC816 CherryMAX Process Manual. TLC865 CherryMAX Selector Guard. 269C3 CherryMAX Grip Gauge. 670A20 Stem Catcher

Bag. 700A77 Bleeder Bottle. P/N 12-02988



CHERRY CHERRY HAND NIPPER

Used for flush trimming Cherry rivets.

P/N 12-02977



GRIP GAUGE LOCKBOLT

Cherry Grip Gauge Lockbolt. Material thickness & grip.... P/N 12-02979



MAXIBOLT GRIP GAUGE 269B12

Cherry Maxibolt Grip Gauge 269B12.

P/N 12-02978



CHERRYMAX GRIP GAUGE

Rivet Grip & Diameter Gauge.

P/N 12-00217



POWER RIVETER G746A

Pneumatic-hydraulic tool designed specifically for installation of CherryMAX Bulb, CherryMAX 'AB' wiredraw and CherryLOCK 'A' wiredraw rivets. Ideal for use in rugged shop environments. This tool utilizes straight, offset and right angle pulling heads. A comfortable grip for one handed operation in any position. Stroke: .875". Pulling Force: 1,850 lbs (839 kgs). Weight: 4.25 lbs (1.9 kgs) P/N 12-02991



G84-LS SPLIT POWER RIVETER

Designed for high-speed, reliable installation of the most popular sizes of blind rivets, lockbolts and blind bolts. Fastener installation in many limited access areas and also reduces operator fatigue. This tool installs all Lockbolt, blind bolts and blind rivets to 1/4" diameter, as well as Cherry rivetless nut plate in all sizes. Stroke: 0.53". Pulling Force: 5700 lbs (2608 kgs). Weight: 11.8 lbs (5.4 kgs). P/N 12-03014



LOCKBOLT HEAVY-DUTY POWER RIVETER G87D

Heavy-duty production tool designed for high speed, reliable installation of the most popular sizes of aircraft Lockbolts. Ideal for use in rugged shop environments. By bending the rubber pin deflector sideways, 1-1/2" additional clearance can be obtained. This tool can also be used to install blind bolts and blind rivets. Stroke: 9/16". Pulling Force: 9,500 lbs (4,309 kgs). Weight: 10.75 lbs (4.9 kgs) P/N 12-03016



SPLIT POWER RIVETER G704B-40SH

Installation of CherryMAX rivets in applications with extremely limited access. Equipped with an 8 foot hose. Pulling heads not included with riveter. Hose Length: 8'. Stroke: .518". Pulling Force: 3136 lbs (1423 kgs). Weight: 4.5 lbs (2.0 kgs) (power unit only)..... P/N 12-02987



SPLIT POWER RIVETER G704B-SR

Designed specifically for the installation of CherryMAX rivets in applications with extremely limited access. Equipped with an 3 foot hose. Pulling heads not included with riveter. Hose Length: 3'. Stroke: .518". Pulling Force: 3136 lbs (1423 kgs). Weight: 4.5 lbs (power unit only)..... P/N 12-02989



NUT-PLATE RIVETER G902 (FEED THROUGH)

All-pneumatic tool designed specifically for installation of nut plate rivets. This tool utilizes straight pulling heads which can install 3/32" and 1/8" pull-through type nut plate rivets and 3/32" CherryLOCK 'A' rivets. Stroke: 3/4". Pulling Force: 550 lbs (250 kgs). Weight: 2 lbs (0.9 kgs) P/N 12-03017



NUT-PLATE RIVETER G902-15 (SIDE EJECT)

The G902-15 (side eject) is an all-pneumatic tool designed specifically for installation of nut plate rivets. This tool utilizes straight pulling heads which can install 3/32" and 1/8" pull-through type nut plate rivets and 3/32" CherryLOCK 'A' rivets. Stroke: 3/4". Pulling Force: 550 lbs (250 kgs). Weight: 2 lbs (0.9 kgs)..... P/N 12-03018



CHERRY HAND RIVETER G30

Pulling head is integral part of tool. Great in areas with limited access or power limitations. The G30 is an efficient, compact and lightweight tool for installing Cherry LOCK 'A' rivets. Overall length: 9 1/4" (23.5cm). Weight 0.8 lbs.. P/N 12-02982

CHERRYLOCK POWER RIVETER TOOL KIT G784KT

Includes: • G784 CherryLock Power Riveter - Stroke: 7/8", Pulling Force: 2,600 lbs (1, 179 kgs), Weight: 8 lbs (3.6 kgs) • B36B740 Valve Spring Installation Tool • B37B740 Valve Sleeve Removal Tool • 74DA43 Shift Piston Tool • 680A114 Seal Guide • 680A114 1 1/2" End Cap Socket Wrench • 680A48/49 Clamp Wrench • 700B65 Packing Plug Wrench • 740A43 Power Cylinder Tool • 700A61 Piston Rod Wrench • P1178 Valve Plug Extractor • 700A60 Seal Guide ..P/N 12-03003

TO