

ENGINE TOOLS



S4-1 RACE REMOVAL TOOL

A & P mechanics will find this S4 outer bearing race removal tool to be very effective and well priced. Hemispheres held together by the "O" ring are inserted together behind the bearing race. The pilot is then inserted to expand and lock the halves & push out the race. You'll like its simplicity and ease of use.....P/N 12-17601



S4-2 RACE REMOVAL TOOL

The S4 magneto drive end inner race removal tool works in conjunction with a standard bearing puller. The split gripper ring fits behind and around the race and is captured in the puller ring by 2 opposing set screws. A groove on the puller ring provides the point of attachment for the puller arms. P/N 12-17602



S4-3 RACE REMOVAL TOOL

The S4 magneto seal installation, inner and outer race installation tool is three tools in one and is proportioned in such a way that it is easily accommodated by most small bench arbor presses. P/N 12-17603



MAGNETO ROTOR BEARING SETTING GAUGE

Determines condition of excess bearing clearance and allows for precise adjustment of new bearings to prevent over or under preload. Available with or without dial indicator. Choice of 3/8-16 or 3/8- 24 threaded shaft fittings.

Kit Description	Thread	Part No.	Price
Setting Gauge & Ind.	3/8-16	12-17801	.
Setting Gauge & Ind.	3/8-24	12-17802	.
Setting Gauge & Ind.	Both	12-17803	.
Setting Gauge, No Ind.	3/8-16	12-17901	.
Setting Gauge, No Ind.	3/8-24	12-17902	.

THROTTLE SHAFTBUSHING KNOCKOUT

The throttle shaft bushing removal tool is very competitively priced and will help you avoid a jury-rigged operation that could damage an expensive carburetor body. Now there is no reason not to have one. They are available and affordable..... P/N 12-17400.....



COMPASS ADJUSTING TOOL



The compass screwdriver is a great little tool that is totally non-magnetic, but also overcomes the shortcomings of solid brass or aluminum tools. This tool has a nice hex aluminum handle and a stainless steel driver insert. No need to worry about damaging the tip on a frozen compensator screw, and you can also remove the cover plate screws with the same tool. P/N 12-17300

ENGINE TOOL TRAY



The engine tool tray is designed for aviation enthusiasts who do maintenance on their own aircraft, as well as full time mechanics. This tool tray sits on top of the push rod tubes and is protected by rubber trim on the bottom to eliminate any damage to the aircraft engine. Instead of dropping a screwdriver or a nut down between cylinder baffling, this tool tray will give the mechanic great organization. It allows for spark plug placement, tool placement, as well as all of those pesky nuts and bolts.....P/N 12-04592



ATS PISTON RING COMPRESSOR KIT

The ATS Piston Ring Compressor features a quick-change design to speed up piston ring installation. It includes the famous Hastings Ring-O-Matic® pliers and bands that operate in all positions: not just vertically or horizontally. The pliers incorporate a precision locking action for exact holding and quick release. Complete kit includes the Ring-O-Matic® pliers and one of each of the following size bands: 3-7/8" to 4-1/8", 4-1/8" to 4-1/2", 4-1/2" to 4-3/4", 4-3/4" to 5", 5" to 5-1/4", & 5-1/4" to 5-3/4"

Description	Part No.	Price
Kit	12-03154	.
Compressor Pliers	12-03155	.
Piston Ring Compressor Band 3-7/8"TO 4-1/8"	12-03156	.
Piston Ring Compressor Band 4-1/8"TO 4-1/2"	12-03157	.
Piston Ring Compressor Band 4-1/2"TO 4-3/4"	12-03158	.
Piston Ring Compressor Band 4-3/4"TO 5"	12-03159	.
Piston Ring Compressor Band 5"TO 5-1/4"	12-03160	.
Piston Ring Compressor Band 5-1/4"TO 5-3/4"	12-03161	.



PISTON RING COMPRESSOR SET

The most efficient, versatile and dependable tool of its kind on the market. Designed to operate both vertically and horizontally. Fine-tooth ratcheting lock permits bands to be contracted in extremely small increments. Positive lock insures a free hand. Eliminates broken rings during installation. Set includes compressor pliers and the two bands (1123, 1125).

Part No.	Size	Engine Application
1123	3-7/8" to 4-1/8"	Cont. A-65, C-85, C-90, 0-200, 0-300
1125	4-3/8" to 4-5/8"	Cont. E-225, IO-470

Set.....P/N 12-10900

Individual Band # 1125 for 4-3/8".....P/N 1125

CYLINDER BASE NUT WRENCHES (CONTINENTAL)



Made of top quality tool steel. 12 Point with 1/2" square drive, 13" long. Set of 4P/N 12-11200

or order individual wrenches below.

LYCOMING & CONTINENTAL CYLINDER BASE NUT WRENCHES

Wrench Part #	Size	Engine Application	Price
2882	9/16" Hex	C-85, 0-200, 0-300, G0-300, E-185, E-225, 0 & IO-470, IO-360, IO-520	.
2882-2	1/2" Hex	A-65, C-85, 0-200, 0-300, G0-300, E-185, E-225, IO-360	.
2882-3	5/8" Hex	A-65, 0-470, IO-520	.
2882-4	3/4" Hex	No longer used on Cont.; Used on Lyc. 0-390D, D2 and all wide deck Lyc engines	.

CYLINDER BASE NUT WRENCHES



- For lycoming engines
- For socket type nuts (internal wrenching)
- Standard 1/2" square female drive end
- Made from alloy steel forgings, heat-treated for maximum toughness.

1/2" Allen Head Hex.....P/N 64942

3/8" Allen Head Hex.....P/N 64943

Set of both.....P/N 12-04722



ATS LYCOMING AND CONTINENTAL CYLINDER BASE NUT WRENCHES

The ATS 3882-series Cylinder Base Nut Wrenches are made from forged alloy steel, tempered, and hardened for maximum strength.

Description	Part No.	Price	Description	Part No.	Price
ATS 3882 9/16	12-04977	.	ATS 3882 5/8	12-04976	.
ATS 3882 1/2	12-04975	.	ATS 3882 3/4	12-04978	.



WASHER WRENCH SET

Washer Wrench Set. This is a (4) piece washer wrench set. It's used to hold AN/ aircraft washers to reach into hard to reach areas.....P/N 12-04723